



E-Tender No. MUM/N/EN/ROB/LC-96, dtd 09.11.2020

**For**

**NAME OF WORK: - Construction of Road Over Bridge in lieu of existing LC No.96 at IR KM 196/26-28 between Atul-Valsad Railway station of Virar – Surat Section of Mumbai Division of Western Railway.**

**FINANCIAL BID**

TENDER DOCUMENT

November - 2020

**Employer:  
DEDICATED FREIGHT CORRIDOR CORPORATION OF INDIA LIMITED  
CGM/NORTH/MUMBAI UNIT  
(A GOVERNMENT OF INDIA ENTERPRISE)  
Under  
MINISTRY OF RAILWAYS**

**SUMMARY OF PRICES**

**NAME OF WORK:** - Construction of Road Over Bridge in lieu of existing LC No. 96 at IR KM 196/26-28 between Atul-Valsad Railway station of Virar – Surat Section of Mumbai Division of Western Railway

Sl. No.	Description of works	Cost as per Schedules	Rates to be quoted in figures & words (Clearly mention above / below / at par on Schedules/Items updated DFCCIL Rate / cost given in column 3)
1	2	3	4
1.	Execution of all works as per Schedule "A" (Items as per SOR 2015-16 of State Govt. Gujarat R&B Valsad division.)	₹ 2,21,21,120.62	<b>Rates above / below / at par as per schedules shall be filled separately in online tender.</b>
2.	Execution of all works as per Schedule "B" (NS Items as per State Govt of Gujarat)	₹ 12,65,30,459.61	
3.	Execution of all works as per Schedule "C" (Items as per SOR 2015-16 of State Govt. Gujarat R&B Valsad division.)	₹ 11,24,73,363.00	
4	Execution of all works as per Schedule "D" (NS Items as per Western Railway)	₹ 6,53,14,935.63	
5	Execution of all works as per Schedule "E" (NS Items as per Western Railway )	₹ 11,50,692.32	
6	Execution of all works as per Schedule "F" (USSOR Items as per Western Railway )	₹ 1,06,74,418.33	
	<b>Total</b>	<b>₹ 33,82,64,989.51</b>	

Notes:

- (i) The above prices are inclusive of all taxes, duties, levies, etc. Except GST.
  - a. GST as applicable from time to time on taxable value of each running account bill shall be paid by DFCCIL.
  - b. The contractor should adhere to anti profiteering provisions as per section 171 of the CGST Act. Where due to change in the rates of GST / Change in law, the contractor gets any credits / benefits, the same shall be passed on to DFCCIL by way of reduction in prices.
- (ii) The tenderer should quote single percentage above / par / below for each schedule.
- (iii) If the uniform percentage quoted by the Tenderer does not clearly indicate whether the rates are above/at par/below the estimated rates then through sign convention it will be considered to be on plus side and evaluated accordingly.
- (iv) Rate of item payable to contractor shall be as per above/below/at par on rates of schedule.

**CGM/N/MUMBAI** acting for and on behalf of The President of India invites E-Tenders against Tender No **MUM-N-EN-ROB-LC-96** Closing Date/Time 23/12/2020 15:00 Hrs. Bidders will be able to submit their original/revised bids upto closing date and time only. Manual offers are not allowed against this tender, and any such manual offer received shall be ignored.

## 1. NIT HEADER

<b>Name of Work</b>	Construction of Road Over Bridge in lieu of existing LC No 96 at IR KM 196 26 28 between Atul Valsad Railway station of Virar Surat Section of Mumbai Division of Western Railway		
<b>Bidding type</b>	Normal Tender		
<b>Tender Type</b>	Open	<b>Bidding System</b>	Two Packet System
<b>Tender Closing Date Time</b>	23/12/2020 15:00	<b>Date Time Of Uploading Tender</b>	
<b>Pre-Bid Conference Required</b>	Yes	<b>Pre-Bid Conference Date Time</b>	02/12/2020 11:00
<b>Advertised Value</b>	338264989.51	<b>Tendering Section</b>	TENDER
<b>Bidding Style</b>	Single Rate for Each Schedule	<b>Bidding Unit</b>	
<b>Earnest Money /Bid Security (Rs.)</b>	5000000.00	<b>Validity of Offer ( Days)</b>	120
<b>Tender Doc. Cost (Rs.)</b>	11800.00	<b>Period of Completion</b>	18 Months
<b>Contract Type</b>	Works	<b>Contract Category</b>	Expenditure
<b>Bidding Start Date</b>	09/12/2020	<b>Are Joint Venture (JV) firms allowed to bid</b>	Yes
<b>Ranking Order For Bids</b>	Lowest to Highest	<b>Expenditure Type</b>	Capital (Works)

## 2. SCHEDULE

S.No.	Item Code	Item Qty	Qty Unit	Unit Rate	Basic Value	Escl. (%)	Amount	Bidding Unit	
<b>Schedule A</b> -Execution of all works as per Schedule "A" (Items as per SOR 2015-16 of State Govt. Gujarat R&B Valsad division.)Execution of all works as per Schedule "A" (Items as per SOR 2015-16 of State Govt. Gujarat R&B Valsad division.)Execution of all works as per Schedule A (Items as per SOR 2015-16 of State Govt. of Gujarat R&B Valsad Division)								22121120.62	Above/Below/Par
1	26117C	2.00	Each	32056.39	64112.78	(-) 9.06	58304.16		
	<b>Description:-</b> Clearing and grubbing road land including uprooting rank vegetation grass bushes, shrubs, sapling and trees girth up to 300 mm removal of stumps of trees cut earlier and disposal of unserviceable materials (C) By mechanical means in area of light jungle								
2	27007A	14670.00	cum	318.15	4667260.50	(-) 9.06	4244406.70		
	<b>Description:-</b> Excavation for foundation in sand, gravel, clay soft soils and murrum etc. Including shoring, strutting dewatering as necessary and disposing of the excavated stuff as directed (A) Depth upto 3.0 m and lead upto 100 m for 10 cum with all lead and lift.								
3	27039	4387.00	Metre	3360.27	14741504.49	(-) 9.06	13405924.18		
	<b>Description:-</b> Empty boring through all. sorts of strata for providing 1.20 M dia. R.C.C. bored piles to required depth including providing necessary casting pipe with all plants and equipment's as required complete.								

4	27004AA	2253.00	Sqm	792.85	1786291.05	(-) 9.06	1624453.08	
	<b>Description:-</b> Providing and laying filter media 600mm thick as directed at the back of abutments, returns, RE Wall and wing walls as per detailed specifications.							
5	26161	572.00	Sqm	298.96	171005.12	(-) 9.06	155512.06	
	<b>Description:-</b> Road marking with hot applied thermoplastic compound with reflectorising glass beads on road surface providing and laying hot applied thermoplastic compound 2.5CM thick including reflectorising glass beads @ 250 gms /sq mt area thickness of surface applied glass bead as per IRC ..35 the finished surface to be level uniform and free from streaks and holes.							
6	27087	3.00	Sqm	733.26	2199.78	AT Par	2199.78	
	<b>Description:-</b> Providing Vertical Joints between retaining walls, abutments, etc. (providing Pre-moulded asphalt filler joints as per drawings 12mm)							
7	27098A	18.00	Numbers	506.01	9108.18	AT Par	9108.18	
	<b>Description:-</b> Providing, fabricating and fixing in position GI Drainage Spout arrangements having 100 mm dia. Pipe B class with necessary bend, fixing to GI chamber, GI grating, providing and applying one coat of primer & two coat of anticorrosive paint, etc. complete as per drawing and as per specifications.							
8	11012	5167.00	Kg	39.99	206628.33	AT Par	206628.33	
	<b>Description:-</b> J type M20 Anchor bolt as per drawing including threading as shown in the drawing for standard octagonal pole type BOP 7030 all complete							
9	11001A	41.00	Quintal	6026.67	247093.47	AT Par	247093.47	
	<b>Description:-</b> Structural Steel :- Base plate of 225 x 225 x 16 mm thick with adjustment of hole. MS plate 6mm thick 20mm wide 150mm long including welding to the base plate all complete							
10	14006A	249.00	Sqm	474.70	118200.30	(-) 9.06	107491.35	
	<b>Description:-</b> Providing and laying chequered terrazzo tiles 22mm thick with marble chips of sizes upto 6mm in floors on 25mm thick bed of Lime mortar 1:1.5 (1-Lime putty : 1.5 coarse sand) or C.M. 1:6 (1 -cement :6 - coarse sand) jointed with neat cement slurry mixed with pigment to match the shade of the tiles including rubbing and polishing complete. (A) Light shades using white cement (upto 10 ton)							
11	NHSOR162	226.00	cum	67.67	15293.42	(-) 9.06	13907.84	
	<b>Description:-</b> Removal of existing asphaltic wearing coat comprising of 50 mm thick asphaltic concrete laid over 12mm thick asphalt including disposal with all lift and lead							
12	27100A	232.00	Each	187.86	43583.52	(-) 9.06	39634.85	
	<b>Description:-</b> Providing PVC 100 mm diameter water spouts including necessary iron gratings as per drawings.							
13	NHSOR88	2707.00	Sqm	63.63	172246.41	AT Par	172246.41	
	<b>Description:-</b> Painting two coats after filling the surface with synthetic enamel paint in all shades on crash barrier concrete surfaces.							
14	26048	1.00	Each	841.33	841.33	AT Par	841.33	
	<b>Description:-</b> Providing & fixing ordinary Kilometre stone of precast C.C. 1:2:4 including necessary reinforcement as per I.R.C. type design in C.C. 1:4:8 including letter & paints etc. complete (For N.H., S.H. & M.D.R.)							
15	27101A	2.00	Numbers	955.46	1910.92	(-) 9.06	1737.79	

	<b>Description:-</b> Providing and fixing marble slab including engraving and painting complete.(A) size 75 cm x 60 cm x 4 cm						
16	26089E	11.00	Metre	2097.77	23075.47	AT Par	23075.47
	<b>Description:-</b> Supplying and fixing reinforced concrete heavy duty non-pressure pipes with collars for culverts carrying heavy traffic as per IS 458-1991 specifications including setting the pipes in C.M. 1:2 watering and laying (to level or slopes) of class NP3 of following internal diameters . (vii) 900mm dia.						
17	27001A	178.00	cum	577.72	102834.16	(-) 9.06	93517.39
	<b>Description:-</b> Dismantling the existing structure including removing and stacking the dismantled materials as and where directed. (Chipping and dressing of the RCC piles upto cut-off level (Min. 1 D) including cleaning of reinforcement and removal of dismantled materials, etc. for providing pile caps as directed by Engineer and as per specification. for 1000 & 1200 mm dia. pile.)						
18	23067	2055.00	Metre	531.26	1091739.30	AT Par	1091739.30
	<b>Description:-</b> Providing, laying and jointing in true line and level 110 diameter U.P.V.C (Type B) conforming to IS 13592-1992 with one end plain and other end socketed with rubber ring, & fittings conforming to ISI 14735-1999 of approved make for drainage system pipe line, pipe shall be						
19	26101B	4.00	Numbers	5246.95	20987.80	AT Par	20987.80
	<b>Description:-</b> Providing & Fixing Village name boards made out of 2mm. Aluminium sheet size 90 x 60 cms rectangle per the design of IRC - 67 - 2015 Pre treated with phosphating process & acid etching : coated with one coat of epoxy primer and two coats of best quality epoxy paint reflectorised with retro reflective sheeting as per latest M.O.S.T Specification :Letters and numerals sound be as per IRC-30-1968, 3.1 M long ( 2 no's) Stand post and frame fabricated from suitable size iron angle of 50 x 50 x 5mm : painted with best quality epoxy coating in black and white bends the details of symbol or inscription / numerals for each board shall be as per the instruction for of Engineer-in-charge, The fixing at site shall be in 1;2;4 CC block of size 45 x 45 x 60cms. for each leg. including excavation curing etc. comp. under the supervision of engineer in charge.(B) High intensity Grade						
20	26103B	8.00	Numbers	6618.53	52948.24	AT Par	52948.24
	<b>Description:-</b> Providing & Fixing sign boards made out of 2mm. Aluminium sheet size 1 Meter x 1 Meter cms as per the design given by engineer in charge, Pre treated with phosphating process & acid etching : coated with one coat of epoxy primer and two coats of best quality epoxy paint reflectorised with retro reflective sheeting as per latest M.O.S.T Specification, Letters and numerals should be as per IRC -30-2015, 3.1 M long ( 2 nos) Stand post and frame fabricated from suitable size iron angle of 35 x 35 3mm & 50 x 50 x 5mm 75 x 75 x 6mm : painted with best quality epoxy coating in black and white bends the details of symbol or inscription / numerals for each board shall be as per the instruction for of Engineer-in-charge, The fixing at site shall be in 1;2;4 CC block of size 45 x 45 x 60cms. for each leg. including excavation curing etc. comp. under the supervision of engineer in charge.(B) High intensity Grade						
21	26098B	2.00	Each	18047.69	36095.38	AT Par	36095.38
	<b>Description:-</b> Providing and fixing Junction Board made out of 2mm aluminium sheet, size 244 x 122 cms rectangle, as per the design of IRC-67-2015. Pre treated with phosphating process and acid etching coated with one coat of epoxy primer and two coats of best quality epoxy paint, reflectorized with retro reflective sheeting as per the latest M.O.S.T. specification, Letters and numerals should be as per IRC-30-1968. 3.1 Mt. long (2 nos.) stand post and frame fabricated from suitable size iron angle of 50 x 50 x 5 mm, 75 x 75 x 6 mm; painted with best quality epoxy coating in black and white bends. The details of symbol or inscription/ numerals for each board shall be as per the instruction of engineer in charge. The fixing at site shall be in 1:2:4 CC block of size 45 x 45 x 60 cms for each leg, including excavation curing etc. complete under the supervision of Engineer-In-Charge (B) . High intensity Grade						
	26102B	12.00	Numbers	2935.06	35220.72	AT Par	35220.72

22	<b>Description:-</b> Hazard Marker Sign :-Providing and fixing sing boards made out of 2mm aluminium sheet; size 90 x 30cms. rectangle as as per the design/drawing attached (IRC) pretreated with phospheting process & acid etching; coated with one coat of epoxy primer and two coats of best quality epoxy paint; reflectorised with retro reflective sheeting as per latest M.O.S.T. Specifications; 3.1m long stand post and frame fabricated from suitable size iron angle of 35 x 35 x 3mm & 50 x 50 x 5mm painted with best quality epoxy coatings The fixing at site shall be in 1:2:4 CC block of size 45x45x 60cms. for each leg. including excavation curing etc. complete under the supervision of engineer in charge.(B)High Intensity Grade							
23	26092B	2.00	Numbers	3272.40	6544.80	AT Par	6544.80	
	<b>Description:-</b> Providing and fixing cautionay warning sign board made of 2mm aluminium sheet size 90X90X90 cms. Equilateral traingle as per the design of IRC-67-2015 pretreated with phospheting process & acid catching with one coat of epoxy primer and two coats of best quality epoxy paint reflectioned with retro reflective sheeting as per latest MOST specification 3.1 mt. long stand post and frame fabricated from suitable size iron angle of 35x35x3mm. 75x75x6mm as required .painted with best quality epoxy coating in black and white bends, the details of symbol for board shall be as per the instruction of engineer-in-charge. the fixing at site shall be in 1;2:4 cc block of size 45X45X60 cms for each leg including excavation curing etc. complete under the supervision of engineer in charge (high intensity grade).							
24	26008	4521.00	cum	66.05	298612.05	AT Par	298612.05	
	<b>Description:-</b> Box cutting the road surface to proper slope and camber for making a base for road work including removing the excavated stuff and depositing on the road side slope as directed.							
25	26163	506.00	Numbers	375.72	190114.32	(-) 9.06	172889.96	
	<b>Description:-</b> Supplying and fixing cat eye with nail less surface (Stimsonite) made out from Acrylic butyle styrene high compression injection moulding with reflector made of MMC (prismatic type of size 12cm x 6cm x 2.5cm) provided with bituminous adhesive 100g. with each unit for fixing. (High Intensity grade)							

S.No.	Item Code	Item Qty	Qty Unit	Unit Rate	Basic Value	Escl. (%)	Amount	Bidding Unit
<b>Schedule B-Execution of all works as per Schedule B (NS items as per State Govt. of Gujarat)</b>							126530459.61	Above/Below/Par
1	StateNS1	1.00	Lumpsum	13108.54	13108.54	AT Par	13108.54	
	<b>Description:-</b> Marking out the center line of the Bridge and various other component structures and complete lining out and levelling with theodolite, levels, including constructing necessary masonry pillars for lines and levels and establishing necessary bench marks etc. complete as directed.							
2	StateNS2	1805.00	cum	243.41	439355.05	AT Par	439355.05	
	<b>Description:-</b> Earth work for embankment including breaking clods dressing With all lead and lift and including watering, rolling, and consolidation of subgrade in layers at O.MC. to required dry density including filling the depressing which occur during the process using Vibratory roller 8.T. to 10 T (from borrow area within 5 km lead).							
3	StateNS3	4550.00	cum	4372.17	19893373.50	AT Par	19893373.50	
	<b>Description:-</b> Providing and laying controlled cement concrete M 35 for R.C.C. bored piles of 1.20 M dia. Including ramming, vibrating and finishing, excluding T.M.T Reinforcement complete.							
4	StateNS4	2022.00	cum	4093.64	8277340.08	AT Par	8277340.08	
	<b>Description:-</b> Providing and casting in-situ controlled cement concrete of M35 grade for RCC work for Pile cap, foundation for pier, abutment, RCC Stair Case and retaining walls with 20/40mm down coarse aggregate of the required size for any depth including dewatering, scaffolding centring, shuttering, mixing, placing in position, consolidating with mechanical vibrators, curing, deshuttering carefully, making good the damages, fixing embedment, inserts, pockets, wherever necessary as per specification and drawing.							

5	StateNS5	1079.00	cum	2723.01	2938127.79	AT Par	2938127.79
	<b>Description:-</b> Providing & filling in foundation with ordinary cement concrete M 15 mix and providing necessary vertical pin headers including formwork vibrating ramming & curing complete						
6	StateNS6	2462.00	cum	4157.61	10236035.82	AT Par	10236035.82
	<b>Description:-</b> Providing and casting in situ controlled cement M35 for RCC work in piers and abutment return wall as per drawing including centring shuttering scaffolding where necessary currying vibrating curing and finishing complete.A)height from 0.0 to 5.0 m						
7	StateNS7	387.28	cum	4388.32	1699508.57	AT Par	1699508.57
	<b>Description:-</b> providing and casting in situ controlled cement M35 for RCC work in piers and abutment return wall as per drawing including centring shuttering scaffolding where necessary laying vibrating curing and finishing complete. A) height above 5.0m.						
8	StateNS8	1026.00	cum	4212.14	4321655.64	AT Par	4321655.64
	<b>Description:-</b> Providing and casting in situ-controlled cement concrete M35 for RCC works on pier cap, abutment cap and dirt wall including controlled cement concrete or pedestals of required drawings, centring shuttering, scaffolding wherever necessary laying vibrating curing and finishing complete.						
9	StateNS9	934.00	cum	4312.82	4028173.88	AT Par	4028173.88
	<b>Description:-</b> Providing and casting in situ controlled cement concrete M40 for RCC works for Pedestal, Seismic Arrestor, Wearing Coat and Deck Slab including controlled cement concrete or pedestals of required drawings, centring shuttering, scaffolding wherever necessary laying vibrating curing and finishing complete .						
10	StateNS10	3336.00	cum	4312.82	14387567.52	AT Par	14387567.52
	<b>Description:-</b> Providing and casting in situ controlled cement concrete M-35 for R.C.C. work in superstructure including centring, shuttering scaffolding, ramming, vibrating curing and finishing complete.(A) T-Beam and Deck slab type of superstructure. (I) Deck slab (II)Main and cross Girder						
11	StateNS11	50.00	cum	3204.00	160200.00	AT Par	160200.00
	<b>Description:-</b> Providing and casting in -situ controlled cement concrete of M 30 grade for Parapet with 20 mm down coarse aggregate of the required size including formwork, shuttering, placing in position, consolidation with mechanical vibrators curing finishing, deshuttering carefully, marking good the damages, fixing embedment, inserts, pockets, wherever necessary as directed and as per drawing with F3 type exposed concrete finish and formwork as directed by Engineer - in -charge, etc. Complete as per specification.						
12	StateNS12	2666.00	Sqm	6140.34	16370146.44	AT Par	16370146.44
	<b>Description:-</b> Reinforced earth Retaining wall(Reinforced Earth Retaining Walls for have for main components as under: a)Excavation for foundation, Foundation concrete & cement concrete grooved seating in the foundation for facing elements (facia material) ,b)Facia material & its placement c)Assembling, joining with facing elements and laying of the reinforcing elements, d) earth fill with granular material which is to be retained by the wall. Facing elements of RCC						
13	StateNS13	17689.00	cum	726.74	12855303.86	AT Par	12855303.86
	<b>Description:-</b> Backfilling, grading and compaction with selected backfill soil in layers in soil Reinforced works with peak internal angle of friction as per adopted design parameters, complete as per drawings and Technical Specifications or as directed by Engineer.						
14	StateNS14	210.00	Metre	846.01	177662.10	AT Par	177662.10
	<b>Description:-</b> Providing and fixing 100 dia runner and down take GI pipe to drain water from drainage spout with necessary fixtures including cost of all materials, labours, bends, fixtures, specials etc. Complete as per drawing and Sp. And as per direction of engineer.						
	StateNS15	3261.00	cum	778.12	2537449.32	AT Par	2537449.32



15	<b>Description:-</b> Construction of 300 mm thick Granular Coarse Sub Base (GSB) (Grade - I crushed B.T materials of 53mm to 9.5mm @ 50% 9.5mm to 2.36mm @ 20%, below 2.36mm @ 30%) by providing coarse graded material mixing in a mechanical mix plant at OMC, carriage of a mix material to work site spreading in uniform layers with motor grader on prepared surface, and compacting with vibratory rollers to achieve the desired density, complete as per MORTH specification						
16	StateNS16	4076.00	cum	832.65	3393881.40	AT Par	3393881.40
	<b>Description:-</b> Providing and laying wet mix base course macadam 250 mm in Two layer using machine crushed chips as per required gradation mixing with required optimum quantity of water conveying the mix to site and spreading to grade and camber with mechanical paver consolidation by vibratory roller including material, labour, plant and machinery and equipment etc. complete.						
17	StateNS17	1468.00	cum	4416.00	6482688.00	AT Par	6482688.00
	<b>Description:-</b> Providing & laying DENSE GRADED BITUMINOUS MACADAM with batch type Drum Mix Plant (DMP) using crushed aggregates of specified grading, premix with bitumen grade 60/70 , bituminous binder @ 5.0 per cent by weight of total mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction complete, including providing & laying tack coat 2.5kg /10sqm all as per MORTH specification.						
18	StateNS18	490.00	cum	4728.51	2316969.90	AT Par	2316969.90
	<b>Description:-</b> Providing and laying 40 mm Bitumen concrete using crushed stone aggregate BT chips as per required gradation and using emulsion asphalt as a tack coat @ 2.5 kg / 10 sqmt and the VG 30 grade asphalt at 55 kg/MT)by total weight of mix hot laid process using drum mix plant including heating and mixing asphalt & materials by drum mix process transporting the mix and laying by paver finisher including consolidation with vibratory roller including cost of material, labour, machinery equipment and fuel , oil , lubricant for plant and machinery using contractor's own plant and machineries etc. complete as per MORTH Specifications						
19	StateNS19	16304.00	Sqm	22.02	359014.08	AT Par	359014.08
	<b>Description:-</b> Providing and applying priming coat with emulsion SS1 grade at the rate of 7.50 kg/ 10 Sq.mt. including cost of asphalt and preparing the surface heating, and applying etc. complete.						
20	StateNS20	20.00	cum	4144.08	82881.60	AT Par	82881.60
	<b>Description:-</b> Providing and casting in situ-controlled cement concrete concrete M-30 for approach slab including formwork curing and finishing complete.						
21	StateNS21	1775.00	Sqm	189.81	336912.75	AT Par	336912.75
	<b>Description:-</b> Providing and applying one coat of Epoxy phenolic primer of DFT 50 microns and two coats of Epoxy phenolic coating of DFT 100 microns each for RCC Element or any other equivalent epoxy coating system to all concrete surfaces exposed to atmosphere in substructure and superstructure including cost of material labour, transportation, scaffolding and preparing the surface by cleaning, washing, brushing, sand/grit blasting etc complete and as directed by engineer and as per specification. (Paint shall be approved from Engineer and tested from approved Laboratory) (Total DFT = 50+100+100 = 250 microns)						
22	StateNS22	278.00	Metre	9410.88	2616224.64	AT Par	2616224.64
	<b>Description:-</b> Providing and fixing in position Strip Seal Type Expansion Joint (for movement up to 60mm) as per detailed drawing MORTH specification. The rate is inclusive of supplying, fixing with contractor's own materials, equipment, machineries, labour, transport, testing, bolts, socket tubes, neoprene sheet/cap etc. complete. The rate is finished item complete and will be paid after fixing in all respect. The Contractor shall procure Strip Seal Expansion Joint, confirming to relevant MORTH specification from M/s.Sanfield (India) Ltd. /METCO or from reputed manufactures of Strip Seal Expansion Joint with prior approval of Engineer-incharge.						
23	StateNS23	2.00	Numbers	3772.00	7544.00	AT Par	7544.00

23	<b>Description:-</b> Providing Pylon consist of cast-in-situ concrete of M30grade exposed finish as per drawing and as directed by engineer in charge. Rate includes providing required shuttering and form work but excluding stone slab & carving. (Reinforcement shall be paid in respective item.)							
	StateNS24	36.00	cum	3772.00	135792.00	AT Par	135792.00	
24	<b>Description:-</b> Providing and casting in situ reinforced cement concrete M30 grade controlled cement concrete in kerb, protection wall around pier, etc. using 6mm to 20mm machine crushed well graded stone aggregate, sand of approved quality, OPC 53 grade cement with contractor's own concrete mix design as approved by client etc complete as per specification. The rate is inclusive of all materials, including necessary mixing in fully automatic batch mix plant, transportation, curing, vibrating, placing in position, shuttering, formwork, deshuttering carefully, making good the damages, fixing embedment, inserts, pockets, wherever necessary, with all lead & lift with contractors labour, tools & plants machinaries, as required with F3/U3 type exposed concrete finish and form mark							
	StateNS25	1330.00	Metre	3612.61	4804771.30	AT Par	4804771.30	
25	<b>Description:-</b> Reinforced Cement Concrete Crash Barrier (Provision of an Reinforced cement concrete crash barrier at the edges of the road, approaches to bridge structures and medians, constructed with M-40 grade concrete with TMT reinforcement conforming to IRC:21 and dowel bars 25 mm dia, 450 mm long at expansion joints filled with pre-moulded asphalt filler board, keyed to the structure on which it is built and installed as per design given in the enclosure to MOST circular No. RW/NH - 33022/1/94-DO III dated 24 June 1994 as per dimensions in the approved drawing and at locations directed by the Engineer, all as specified) & Provide 150 mm dia PVC pipe for utility services etc complete (A) Only crash barrier							
	StateNS26	657.00	Metre	7617.43	5004651.51	AT Par	5004651.51	
26	<b>Description:-</b> Reinforced Cement Concrete Crash Barrier (Provision of an Reinforced cement concrete crash barrier at the edges of the road, approaches to bridge structures and medians, constructed with M-40 grade concrete with TMT reinforcement conforming to IRC:21 and dowel bars 25 mm dia, 450 mm long at expansion joints filled with pre-moulded asphalt filler board, keyed to the structure on which it is built and installed as per design given in the enclosure to MOST circular No. RW/NH - 33022/1/94-DO III dated 24 June 1994 as per dimensions in the approved drawing and at locations directed by the Engineer, all as specified) & Provide 150 mm dia PVC pipe for utility services etc complete (A) crash barrier with Friction slab							
	StateNS27	14528.00	Sqm	182.69	2654120.32	AT Par	2654120.32	
27	<b>Description:-</b> PRIMER & PROTECTIVE COATING-providing and laying the external decorative waterproof & Protective coating system for concrete and masonry shall be MASTERSEAL 200H, a single component elastomeric crack bridging acrylic coating applied at an average thickness of 50 micro DFT in two coat the product shall be applied on suitability primed substrate using MASTERSEAL 399 as primer. The product must be crack bridging elongation type with elongation at break, exceeding 200% & tensile strength exceeding 2 MPa The system shall exhibit excellent bond strength with the substrate at least exceeding 1.0 MPa, when tested as per ASTM D 4541.							

S.No.	Item Code	Item Qty	Qty Unit	Unit Rate	Basic Value	Escl. (%)	Amount	Bidding Unit
<b>Schedule C-Execution of all works as per Schedule C (Items as per SOR 2015-16 of State Govt. of Gujarat R&amp;B Valsad Division)</b>							112473363.00	Above/Below/Par
1	27020A	151.00	MT	44690.48	6748262.48	6.89	7213217.76	
	<b>Description:-</b> Providing and installing 6 mm MS liner for bored-cast-in-situ concrete piles including applying protective coating as per drawing and specification and as directed by Engineer.							
	27043C	718.00	MT	44549.08	31986239.44	12.86	36099669.83	

6	<b>Description:-</b> Providing and placing in position High Yield Strength Deformed (HYSD) bars reinforcement (TMT Fe 500D grade) conforming to IS 1786 of all categories for Pile including cutting, bending, hooking and tying with 18 gauge mild steel binding wires, supporting in position to ensure lines and levels during concreting, maintaining proper cover / spacing etc. complete as per specification and detailed drawing.							
3	27047A	333.00	MT	42446.26	14134604.58	12.86	15952314.73	
	<b>Description:-</b> Providing and placing in position High Yield Strength Deformed (HYSD) bars reinforcement (TMT Fe 500D grade) conforming to IS 1786 of all categories for Pile cap, foundation for pier/ abutment/ return wall including cutting, bending, hooking and tying with 18 gauge mild steel binding wires, supporting in position to ensure lines and levels during concreting, maintaining proper cover / spacing etc. complete as per specification and detailed drawing.							
4	2710927111	612.00	MT	45575.24	27892046.88	12.86	31478964.11	
	<b>Description:-</b> Providing and placing in position High Yield Strength Deformed (HYSD) bars reinforcement (TMT Fe 500D grade) conforming to IS 1786 of all categories for pier, abutment, pier cap, abutment cap, returns, pedestal, seismic arrester & retaining wall including cutting, bending, hooking and tying with 18 gauge mild steel binding wires, supporting in position to ensure lines and levels during concreting, maintaining proper cover / spacing etc. complete as per specification and detailed drawing.							
5	27121	363.00	MT	44990.45	16331533.35	12.86	18431768.54	
	<b>Description:-</b> Providing and placing in position High Yield Strength Deformed (HYSD) bars reinforcement (TMT Fe 500D grade) conforming to IS 1786 of all categories for superstructure including cutting, bending, hooking and tying with 18 gauge mild steel binding wires, supporting in position to ensure lines and levels during concreting, maintaining proper cover / spacing etc. complete as per specification and detailed drawing.							
6	27123	62.00	MT	44298.60	2746513.20	12.86	3099714.80	
	<b>Description:-</b> Providing and fixing in position steel bar reinforcement of steel grade Fe-500 (TMT) including cutting ,bending, hooking, tying, welding etc, complete as per detailed drawing and specification (A) R.C.C. Approach slab , (B) Wearing Coat							
7	NHSOR823B	50.00	Metre	3503.69	175184.50	12.86	197713.23	
	<b>Description:-</b> Providing and erecting a "Thrie" metal beam crash barrier comprising of 3 mm thick corrugated sheet metal beam rail, 85 cm above road/ground level, fixed on ISMC series channel vertical post, 150 x 75 x 5 mm spaced 2 m centre to centre, 2 m high with 1.15 m below ground level, all steel parts and fitments to be galvanised by hot dip process, all fittings to conform to IS:1367 and IS:1364, metal beam rail to be fixed on the vertical post with a space of channel section 150 x 75 x 5 mm, 546 mm long complete as per clause 810							

S.No.	Item Code	Item Qty	Qty Unit	Unit Rate	Basic Value	Escl. (%)	Amount	Bidding Unit
<b>Schedule D-Execution of all works as per Schedule D (NS items as per Western Railway)</b>							65314935.63	Above/Below/Par
	NS1	396.42	MT	98897.53	39204958.84	AT Par	39204958.84	

1	<p><b>Description:-</b> Supply &amp; Fabrication of steel girder spans including its components (Stiffeners, Bracings, Splices, Studs etc.) as per the approved drawings for composite construction of superstructure of the Road Over Bridge with contractor's own Steel conforming to IS: 2062 Grade 250/350(B0) with all welds, HSFG Bolts, nuts bolts, rivets etc. with contractor's own materials, fabrication, machinery, templates, fixtures, equipment tools and plants transportation, skilled/unskilled labour, excise duty., Octroi, sales tax and other taxes, all leads lifts, descent, loading, unloading, crossing one or more Railway track if required etc. complete and as per technical specifications. The rate is inclusive of transportation of fabricated girder parts to site by contractor's own means at his cost. The rate shall also be inclusive of cold straightening of deformed and bent girder parts before their assembly. (The Structural Steel to be used Should be manufactured by SAIL/RINL/TISCO/ESSAR/JINDAL Only.)Work has to be done as per drawings and specifications approved by DFCCIL/ Railway. High quality superior brand of paint should only be used. For Painting prior approval for superior brand / make of the paint should be taken from engineer in charge. Note:1. The fabrication of girders must be got done from RDSO approved firms only. 2. The rate is inclusive of assembly of girder with service bolts as per approved drawing in shop for checking by Engineer's representative and dismantling the same after checking for transportation to the site. 3. Weight of HSFG bolts, Rivets, Welds shall not be considered for payment. Nominal weight of the girder spans including its components (Stiffeners, Bracings, Splices, Studs etc.) as per drawing will only be considered for payment.</p>						
2	NS2	6300.00	Sqm	682.79	4301577.00	AT Par	4301577.00
	<p><b>Description:-</b> Metalizing girder / girder components such as cross girders, top chord channels, bracing etc. of Steel Girder as directed by Engineer with aluminium spray not less than two layers after preparing surface by sand/grit blasting as per provision laid in Appendix VI of IRS B 1179 code (latest alteration) including one coat wash primer (IS-5666) one coat zinc chrome primer (IS-104) and two coats of aluminium paint (IS-2339) with approved paint conforming to IS specification for fabrication &amp; erection of steel girder bridge (RS B 1-79) as corrected up to date with contractor's own materials, tools, plants labour, loading/unloading, transportation, handling, re-handling if any including all lead, lifts descents, crossing of track/obstruction etc. complete in all respect and as per direction of the Engineer.</p>						
3	NS3A	360.38	MT	18924.10	6819867.16	AT Par	6819867.16
	<p><b>Description:-</b> Assembling, Welding, Erecting, Bolting by HSFG bolts, Riveting if any as per approved drawings and Launching of girder spans including its components on running line / Non-Running line /Running electrified line / under block period with the help of road crane of required capacity as per Railway's approved drawings &amp; Scheme with other ancillary steel structures fixed to the girder, where necessary, in proper level and alignment and as per technical specifications. The rate shall be inclusive of supply, erection and dismantling of staging and scaffolding and other temporary arrangements required for the purpose of assembly, erection and launching of girders. The rate shall also be inclusive of cold straightening of deformed and bent girder parts before/after their assembly. Work has to be done as per drawings and specifications approved by Railway.Note: Weight of HSFG bolts, Rivets, Welds shall not be considered for payment. Nominal weight of the girder spans including its components (Stiffeners, Bracings, Splices, Studs etc.) as per drawing will only be considered for payment.Launching of Steel girder spans including its components on running line /Running electrified line / under block period with the help of road crane of required capacity as per Railway's approved drawings with other ancillary steel structures fixed to the girder where necessary in proper level and alignment and as per technical specifications.</p>						
3	NS3B	36.04	MT	3577.88	128946.80	AT Par	128946.80
	<p><b>Description:-</b> launching of steel girder spans including its components on non- running line with the help of road crane of required capacity as per Railway's approved drawings with other ancillary steel structures fixed to the girder where necessary in proper level and alignment and as per technical specifications.</p>						
	NS4	19.00	MT	79040.07	1501761.33	AT Par	1501761.33

4	<b>Description:-</b> Fabricating, supplying and erecting in position standard structural steel sections manufactured from IS approved manufacturers only ,conforming to IS :2062 - 1992 (including latest amendments) including welding with approved quality welding rods, supply and fixing of correct size turn bolts including one primer coat of red lead paint conforming to IS:102 or Zinc chromate paint conforming to IS:104 followed by tow coats of Aluminium paint as per IS : 2339 with all contractor's materials, labour, tools and plants etc in bolted/welded construction as directed by Engineer in charge. Work shall be carried out as per IS:800-1984 (with latest amendments), IRS specification No. B3-61 part 2 and IS 816 for welding.						
6	NS6	1.00	Each	288304.70	288304.70	AT Par	288304.70
	<b>Description:-</b> Load testing of one composite steel/ Span Designing and Load testing of one composite girder/ Span as selected by the Engineer confirming to Rly. Standard's with loads to be applied and removed incrementally etc. complete as per special condition and specification of contract, as per relevent IS/IRC codes with all contactors labour supervisor, T & P's all taxes, equipment, leading materials instruction of load test jacks etc., dial gauges, including all lead and lift.						
7	NS7	134.00	Each	1349.21	180794.14	AT Par	180794.14
	<b>Description:-</b> Conducting Pile low strain integrity test as per ASTM D 5882- 96 code of American Society for Testing on cast -in situ RCC pile of 1200 mm diameter inclusive of analysis with all contractor's equipment, manpower, site preparation, lead and lifts etc. complete as per standard procedure, and as directed by the Engineer in charge. Note:- Rate is inclusive All equipment, All labour and consumable required & Mobilization of equipment						
05	NS5B	119.00	Numbers	60227.69	7167095.11	AT Par	7167095.11
	<b>Description:-</b> NS/5b) Sliding bearing (Capacity upto 250 MT)Note: The rate is for finished item complete and paid only after fixing in position below the girder.						
005	NS5A	95.00	Numbers	60227.69	5721630.55	AT Par	5721630.55
	<b>Description:-</b> Providing and fixing POT -PTFE bearing as per IRC 83 in position true to line and level including cost of all materials fixtures surface for receiving bearing, grouting of sleeves with non shrink high strength grout, load testing of bearing, transporing and fixing in position including all lead and lift etc. complete as per approved designs and drawing and as directed by Engineer.NS/5a) Fixed bearing (Capacity upto 250 MT)						

S.No.	Item Code	Item Qty	Qty Unit	Unit Rate	Basic Value	Escl. (%)	Amount	Bidding Unit
<b>Schedule E-Execution of all works as per Schedule E (NS items as per Western Railway)</b>							1150692.32	Above/Below/Par
1	NS1	109916.00	Sqm	0.40	43966.40	(-) 8.36	40290.81	
	<b>Description:-</b> AutoCAD Drawings : Preparation / Alternation and submission of drawings such as general arrangement drawings , phase drawings, scheme plan, structural drawings etc. On Auto CAD as per details and directions given by the Engineer in charge including plotting and submitting in standard inklet film of 50 micron and CD, submitting check prints on A3/A2/A0 size papers and final print complete and as per instructions of Engineer in charge.							
2	NS2	1.00	Lumpsum	500000.00	500000.00	(-) 8.36	458200.00	
	<b>Description:-</b> Site Office Providing, arranging, managing and maintaining 500 sq.ft. well-furnished AC office and well equipped Laboratory with 3 tables, 10 chairs, 2 steel almira, one computer with printer & operator, sufficient number of display etc. to the satisfaction of the Project Manager including Electrical, Water expenses etc. For execution of this item the date of start shall be considered only when the Contractor has actually rented/constructed the required premises established the office & Laboratory as per requirement. This item shall remain valid only for original contact period; no additional payment shall be made for whatsoever reason even if time extension if provided or date of completion is extended. This office and laboratory including furniture and all other equipment shall be property of contractor after completion of Project.							

3	NS3	166.00	Sqm	1179.80	195846.80	(-) 8.36	179474.01	
	<b>Description:-</b> Providing & fixing Safety Screen as per RDSO Drg. No. EL / C / 0068 MOD " E " , on the Parapet with necessary fixtures etc. as per detailed drawing including contractor's own materials, labours, tools and plants, etc. complete.							
4	NS4	4.00	Each	2997.00	11988.00	(-) 8.36	10985.80	
	<b>Description:-</b> Making and supplying of check rails of 52 kg/ 60 kg rails of various lengths for level crossing as per approval drawings.							
5	NS5	1520.00	Metre	331.49	503864.80	(-) 8.36	461741.70	
	<b>Description:-</b> Providing, fixing and maintaining MS fabricated traffic barricading of 2.50m height on either side of the carriage way / portion of the carriage way closed to the traffic including provision of all sign boards/ bollards and warning lights etc. as per the Engineer in charge.							

S.No.	Item Code	Item Qty	Qty Unit	Unit Rate	Basic Value	Escl. (%)	Amount	Bidding Unit
<b>Schedule F-Execution of all works as per Schedule F (USSOR items as per Western Railway)</b>							10674418.33	Above/Below/Par
1	192103	5.00	Each	197745.38	988726.90	AT Par	988726.90	
	<b>Description:-</b> Conducting load testing of a single pile up to following capacity in accordance with IS 2911 (Part IV) including installation of loading platform and preparation of pile head or construction of test cap and dismantling of test cap after test etc with all labour material, tool & plant , equipment, machinery etc complete as per drawing and specification as directed by the Engineer.Initial load test above 100 ton capacity up to 250 ton capacity. USSOR 2011 western railway item no.192103Upto 250 tonne							
2	192104	100.00	Each	43817.59	4381759.00	AT Par	4381759.00	
	<b>Description:-</b> Extra over 50 t							
3	192107	5.00	Each	277267.47	1386337.35	AT Par	1386337.35	
	<b>Description:-</b> Routine load test above 100 ton capacity up to 250 ton capacity pile. USSOR 2011 western railway item no.192107Up to 250 tonne							
4	192107	50.00	Each	43817.59	2190879.50	AT Par	2190879.50	
	<b>Description:-</b> Routine load test above 100 ton capacity up to 250 ton capacity pile. USSOR 2011 western railway item no.192107Extra over 50 t							
5	191050	4.00	Each	10453.50	41814.00	AT Par	41814.00	
	<b>Description:-</b> Conducting in situ size Plate Load Test (PLT) at selected location as per IS : 1888 including making loading arrangements & casting of RCC/cast in situ concrete footing as per codal provisions including excavation and refilling of trial pit.							
6	192110	6.00	Each	174625.72	1047754.32	AT Par	1047754.32	
	<b>Description:-</b> Lateral Load Testing of single pile in accordance with " IS Code of practice IS: 2911 (Part IV) for determining safe allowable lateral load of pile" with all labour, material, tool & plants, equipment, machinery, etc complete as per drawing and specification as directed by the engineer.Piles with lateral load capacity of up to 10 ton							
7	192112	6.00	Each	58702.21	352213.26	AT Par	352213.26	
	<b>Description:-</b> Lateral Load Testing of single pile in accordance with " IS Code of practice IS: 2911 (Part IV) for determining safe allowable lateral load of pile" with all labour, material, tool & plants, equipment, machinery, etc complete as per drawing and specification as directed by the engineer.Piles with lateral load capacity of above 10 ton & up to 20 ton							
	201051	26.00	Metre	10959.00	284934.00	AT Par	284934.00	

8	<b>Description:-</b> Providing and fixing in position of standard performed sealed and slab type or Strip Seal elastomeric Type Expansion Joints (80 mm expansion) for railway bridge or Road over Bridge as per approved drawing and latest MORTH/IRC 69 specification. The rate are inclusive of supplying, fixing with contractor's own materials e.g. inserts, bolts, socket tubes, neoprene sheet/cap etc. equipment, machineries, labour, all taxes, royalty, all lead and lift, transport, testing, surface preparations, complete.
---	--

### 3. ITEM BREAKUP

No item break up added
------------------------

### 4. ELIGIBILITY CONDITIONS

**Important** All documents uploaded and remarks / confirmation entered by the bidders against any : eligibility condition shall be opened as part of technical bid only

#### Special Financial Criteria

S.No.	Description	Confirmation Required	Remarks Allowed	Documents Uploading
1	AS PER TENDER DOCUMENTS	No	No	Allowed (Mandatory)

#### Special Technical Criteria

S.No.	Description	Confirmation Required	Remarks Allowed	Documents Uploading
1	AS PER TENDER DOCUMENTS	No	No	Allowed (Mandatory)

### 5. COMPLIANCE

**Important** All documents uploaded and remarks / confirmation entered by the bidders against any : compliance condition shall be opened as part of technical bid only.

#### Check Lst

S.No.	Description	Confirmation Required	Remarks Allowed	Documents Uploading
1	AS PER TENDER DOCUMENTS	No	No	Not Allowed

#### Commercial-Compliance

S.No.	Description	Confirmation Required	Remarks Allowed	Documents Uploading
1	Please enter the percentage of local content in the material being offered. Please enter 0 for fully imported items, and 100 for fully indigenous items. The definition and calculation of local content shall be in accordance with the Make in India policy as incorporated in the tender conditions.	No	Yes	Allowed (Optional)

#### General Instructions

S.No.	Description	Confirmation Required	Remarks Allowed	Documents Uploading
1	AS PER TENDER DOCUMENTS	No	No	Not Allowed

#### 6. Documents attached with tender

S.No.	Document Name	Document Description
1	GAD__APPROACH_PORTION_96.pdf	GAD for Approach Portion
2	ANNEXURE_I_Bidder_96.pdf	Annexure I Bidder
3	Formno2Afor96.pdf	Form no 2A for 96
4	Formno2Bfor96.pdf	Form no 2B for 96
5	GAD__RAILWAY_PORTION_96.pdf	GAD FOR RAILWAY PORTION
6	Financial_Bid_for_96.pdf	Financial Bid for 96
7	Technical_Bid_for_96_09.11.2020.pdf	Technical Bid for 96

**Signed By:** JAGDISH VIJAY RATHOD

**Designation :** DYPM