



GENERAL INFORMATION / DATA SHEET

TENDER NOTICE NO.	DFC/ADI/ENGG/ADI-PNU/ROB/LC.No.204/19
Name of the work	Construction of Road over Bridge including approaches complete in lieu of LC No. 204 at Railway km. 700/3-4 (DFC Ch. 65.270) between Unjha and Bhandu motidau station of Ahmedabad- palanpur section of Western Railway, Ahmedabad Division.
Tender Value	Rs. 56,96,28,000/-
Completion Period	18 months
Earnest Money	Rs. 56,96,280/-
Cost of Tender Document	Rs.29,500/- (25,000 + 18% GST) to be Paid through Demand Draft / Banker's cheque payable in favour of "Dedicated Freight Corridor Corporation of India Limited, Ahmedabad"
Tender Processing Fee	Rs. 7500/- plus taxes and duties as applicable (non-refundable) through e-payment while uploading of tender.
Date and Time of Sale of Tender (Online)	From date 23.08.2019.
Pre Bid conference	On 06.09.2019 at 12.30 Hrs. at CGM-DFCCIL office, Ahmedabad.
Last date and Time of submission of Tender (Online)	23.09.2019 upto 18:00 hrs
Last date and Time of submitting documents in physical form.	27.09.2019 upto 18:00 hrs
Date and Time of Opening of Tender (Technical Bids - Packet A)	On 28.09.2019 at 12:30 hrs
Date and Time of Opening of Financial Bid -Packet B	Will be notified to bidder qualified in Technical bid and also posted on <u>www.tenderwizard.com/DFCCIL</u>
E-Tendering Web site Address:	www.tenderwizard.com/DFCCIL For any help in connection with e-tendering please contact at tenderwizard.com helpdesk No. 011-49424365 or Mobile No. +91- 9599653865/9714881992/080-40482000.
Validity of offer	90 days
Retention Money / Security Deposit	5 % of Contract Value
Performance Bank Guarantee	Performance Guarantee (PG) have to be submitted within 21(Twenty One) days from the date of issue of Letter Of Acceptance (LOA), amounting to 5% of the contract value in the form as give in clause 16.(4) of GCC.
Office Address	Chief General Manager , Dedicated Freight Corridor Corporation of India Limited, B/3rd Floor, 4-D Square Mall, Opp. Vishwkarma Engg. College, Visat-Gandhinagar Highway, Ahmedabad-380005



SUMMARY OF PRICES

Name of work :- Construction of Road over Bridge including approaches complete in lieu of LC No. 204 at Railway km. 700/3-4 (DFC Ch. 65.270) between Unjha and Bhandu motidau station of Ahmedabad-palanpur section of Western Railway, Ahmedabad Division.

Note:- Financial bid (Microsoft Excel file) to be filled, saved and uploaded with digital signature. Only the downloaded financial bid filed should be uploaded after filing and saving. Do not upload scanned copy such as pdf or jpg etc of 'Financial Bid' in document library.

SI. No.	Description of works	Cost as per Schedules	Rates to be quoted online mode in figures & words (Clearly mentioning above / below / at par on Schedules)
1	2	3	4
1.	Execution of all works as per Schedule "A" (Items as per SOR 2015-16 of State Govt. Gujarat R&B Mehsana division.)	Rs. 48925418	as per ately in
2.	Execution of all works as per Schedule " B " (NS Items as per State Govt.)	Rs. 195671315	below / at par as pe be filled separately oft Excel File.
3.	Execution of all works as per Schedule "C" (TMT/Liner NS Items)	Rs. 225156837	filled Excel
4	Execution of all works as per Schedule "D" (USSOR Items as per Western Railway)	Rs. 1596600	bove / below / s shall be filled Microsoft Exce
5	Execution of all works as per Schedule "E" (NS Items as per Western Railway)	Rs. 95367315	- • •
6	Execution of all works as per Schedule "F" (NS Items as per Western Railway etc.)	Rs. 3531208	Rates
	Grand Total	Rs. 570248693	

I / We offer and agree to execute above work at rate uploaded online at <u>www.tenderwizard.com/DFCCIL</u> through digital signature.

Notes:

- (i) The above rates/prices are inclusive of all taxes, inclusive of GST, duties, levies, Royalties etc.
- (ii) The Contractor shall be responsible for deposition of applicable GST to the concerned authority and DFCCIL shall Pay the applicable GST after receipt of GST invoice with on account bill from the contractor.
- (iii) The contractor should adhere to anti profiteering provisions as per section 171 of the CGST Act. Where due to change in the rates of GST/ Change in law, the contractor gets any credits / benefits, the same shall be passed on to DFCCIL by way of reduction in prices.
- (iv) The tenderer should quote single percentage above / par / below for each schedule.
- (v) If the uniform percentage quoted by the Tenderer does not clearly indicate whether the rates are above/at par/below the estimated rates then through sign convention it will be considered to be on plus side and evaluated accordingly.
- (vi) Rate of item payable to contractor shall be as per above/below/at par on rates of schedule.

FORM No. 4

SCHEDULE -1 SCHEDULE OF PRICES & TOTAL PRICES

Name of work :- " Construction of Road over Bridge including approaches complete in lieu of LC No. 204 at Railway km. 700/3-4 (DFC Ch. 65.270) between Unjha and Bhandu motidau station of Ahmedabad-palanpur section of Western Railway, Ahmedabad Division."

Schedule- A

Sr. No.	Item No.	Total Qty.	Item of work	Rate	UNIT	Amount in Rs.
1	26117C	3	Clearing and grubbing road land including uprooting rank vegetation grass bushes, shrubs, sapling and trees girth up to 300 mm removal of stumps of trees cut earlier and disposal of unserviceable materials (C) By mechanical means in area of light jungle	32018.93	На	96057
2	27007A	22359	Excavation for foundation in sand gravel, clay, soft, soils and murrum etc. including soring strutting and dewatering as necessary and dis posing off the excavated stuff as directed (A) up to 3.00 mt depth and lead upto 100m for 10Cum	309.27	Cu.m.	6914968
3	27007B	1543	Excavation for foundation in sand gravel, clay, soft, soils and murrum etc. including soring strutting and dewatering as necessary and dis posing off the excavated stuff as directed. (B)3.00 mt to 6.0mt depth. and lead upto 100m for 10Cum.	362.49	Cu.m.	559322
4	26008	7030	Box cutting the road surface to proper slope and camber for making a base for road work including removing the excavated stuff and depositing on the road side slope as directed upto 50Mt. lead.	66.02	Cu.m.	464121
5	27039	5848	Empty boring through all. sorts of strata for providing 1.20 M dia. R.C.C. bored piles to required depth including providing necessary casting pipe with all plants and equipment's as required complete.	3360.73	RMT	19653549



6	USSOR		Conducting load testing of a single pile]
	192100		Up to following capacity in accordance with IS 2911-IV including installation of loading platform & preparation of pile head or construction of test cap & dismantling of test cap after test etc. with all labour, material, tool & plants, equipment, machinery, etc. complete as per drawing & specification as directed by the Engineer.			
	192103	5	Initial load test Above 100 tonne capacity Upto 250 tonne capacity pile	197745.38	Each	988727
	192104	150	Extra for every increase of 50 t in a pile capacity or part thereof over 250 t.	43817.59	Each	6572639
	192107	5	Routine load test Above 100 tonne capacity Upto 250 tonne capacity pile	277267.47	Each	1386337
7	27072	3096580	Providing and fixing in position fully moulded restrained elastomeric Bearings as per detailed drawings.	1.07	Cu.cm	3313341
8	14018A	374	Providing and laying chequered precast cement concrete tiles 22mm thick with aggregate of sizes upto 6mm in floors, treads of steps and landings on 20mm thick bed of C.M. 1:6 (1-cement : 6-sand) or L.M. 1:1.5(1-Lime putty : 1.5 coarse sand) joint with neat cement slurry with pigments to match the shade of the tiles.	366.08	Sqm	136914
9	27100A	224	Providing PVC. 100 mm. diameter water spouts including necessary iron gratings as per drawings.	187.86	Each	42081
10	NH SOR 14.22	218	Providing and laying of a strip seal expansion joint catering to maximum horizontal movement upto 70 mm complete as per approved drawings and standard specifications to be installed by the manufacturer/supplier or their authorised representative ensuring compliance to the manufacturer's instructions for installation.	1724.07	RMT	375847



11	USSOR 201050		Providing and fixing in position of standard performed sealed and slab type or Strip Seal elastomeric Type Expansion Joints for railway bridge or Road over Bridge as per approved drawing and latest MOST/IRC 69 specification. The rate are inclusive of supplying, fixing with contractor's own materials e.g. inserts, bolts, socket tubes, neoprene sheet/cap etc. equipments, machineries, labour, all taxes, royalty, all lead and lift, transport, testing, surface preparations, complete.			
	201051	59	For 80 mm expansion	10959.03	RMT	646583
12	26089EA	10	Supplying and fixing reinforced concrete heavy duty non-Pressure pipes with collars for culverts carrying heavy traffic as per IS 458-1991 specifications including setting the pipes in C.M. 1:2 watering and laying (to level or slopes) of class NP3 of following internal diameters.(vii) 900mm dia.	2093.71	RMT	20937
13	23067	3364	Providing, laying and jointing in true line and level 110 diameter U.P.V.C (Type B) conforming to IS 13592-1992 with one end plain and other end socketed with rubber ring, & fittings conforming to ISI 14735-1999 of approved make for drainage system pipe line, pipe shall be jointed with each other with rubber lubricant, pipe shall be fixed on wall using of PVC clamp of the size 110 mm diameter x 149 mm length x 145 mm height at every 2000 mm center to center or shall be concealed in walls as directed including necessary fittings such as bends, shoes etc. including testing of pipes and joints and jointed with adhesive solvent cement including cost of all materials.	1172.04	RMT	3942743

14	19033	810	Providing and laying Road marking with hot applied thermo plast compound reflecting class bands on bitumingue	299.36	Sq.m.	242482
			reflecting glass bends on bituminous surface. Providing and laying Hot applied thermoplastic compound 2.5 cm thick			
			including reflectorizing glass bends 250 gms/sqmt area, thickness of surface			
			applied glass bends as per IRC 35 the finished surface to be level uniform and free from streaks & holes.			
15	26101B	4	Providing & Fixing Village name	5401.48	Nos.	21606
			boards made out of 2mm. Aluminium sheet / 4 mm ACP (aluminium composite panel), size 90 x 60 cms rectangle per the design of IRC - 67 - 2012 Pre treated with phosphating process & acid etching : coated with one coat of epoxy primer and two coats of best quality epoxy paint reflectorised with high intensity prismatic grade retro reflective sheeting of type-4 as per ASTM D-4956 and latest M.O.S.T Specification, 3.3 M long (2 no's) Stand post and frame fabricated from suitable size iron angle of 75 x 75 x 6mm/ 65 NB circular MS pipe as required and frame fabricated from suitable size iron angle of 35x35x3mm; painted with best quality epoxy coating in black and white bends the details of symbol or inscription / numerals for each board shall be as per the instruction for of Engineer-in-charge, The fixing at site shall be in 1;2;4 CC block of size 45 x 45 x 60cms. for each leg. including excavation curing etc. comp. under the supervision of engineer in charge.(B) High intensity Grade. A warranty for 7 years for the retro reflective sheeting from original manufacturer and certified copy of three years outdoor exposure test report from third party test lab for the product offered shall be submitted by contractor.(B) Class-B type-4 retro reflective sheeting.			
16	26103B	8	Providing & Fixing sign boards made out of 2mm. Aluminium sheet / 4 mm ACP (aluminium composite panel) size	10464.61	Nos.	83717



I		
	1 Meter x 1 Meter as per the design	
	given by engineer in charge, Pre treated	
	with phosphating process & acid etching	
	: coated with one coat of epoxy primer	
	and two coats of best quality epoxy paint	
	reflectorised with high intensity prismatic	
	grade retro reflective sheeting of type-4	
	as per ASTM D-4956 and as per latest	
	M.O.S.T Specification, , 4.0 M long (2	
	nos) Stand post and frame fabricated	
	from suitable size iron angle of 75 x 75 x	
	6mm / 65 NB circular MS pipe as	
	required and frame fabricated from	
	suitable size iron angle of 50 x 50 x 5mm	
	; painted with best quality epoxy coating	
	in black and white bends the details of	
	symbol or inscription / numerals for	
	each board shall be as per the	
	instruction for of Engineer-in-charge,	
	The fixing at site shall be in 1;2;4 CC	
	block of size 45 x 45 x 60cms. for each	
	leg. including excavation curing etc.	
	comp. under the supervision of engineer	
	in charge.(B) High intensity Grade. A	
	warranty for 7 years for the retro	
	reflective sheeting from original	
	manufacturer and certified copy of three	
	years outdoor exposure test report from	
	third party test lab for the product offered	
	shall be submitted by contractor.(B)	
	Class-B type-4 retro reflective sheeting.	
	,, , , , , , , , , , , , , , , , , , ,	

4-	000005	•		00745.03		45.466
17	26098B	2	Providing and fixing Junction Board	22715.91	Each	45432
			made out of 2mm aluminium sheet / 4			
			mm ACP (aluminium composite panel),			
			size 244 x 122 cms rectangle, as per the			
			design of IRC-67-2012. Pre treated with			
			phosphating process and acid etching			
			coated with one coat of epoxy primer			
			and two coats of best quality epoxy			
			paint, refloctrorized with high intensity			
			prismatic grade retro reflective sheeting			
			of type-4 as per ASTM D-4956 and as			
			per the latest M.O.S.T. specification. 4.0			
			Mt. long (2 nos.) stand post and frame			
			fabricated from suitable size iron angle of			
			$75 \times 75 \times 6$ mm / 65 NB circular MS pipe			
			as required and frame fabricated from			
			suitable size iron angle of 50 x 50 x			
			5mm; painted with best quality epoxy			
			coating in black and white bends. The			
			details of symbol or inscription/ numerals			
			for each board shall be as per the			
			instruction of engineer in charge. The			
			fixing at site shall be in 1:2:4 CC block of			
			size 45 x 45 x 60 cms for each leg,			
			including excavation curing etc. complete			
			under the supervision of Engineer-In-			
			Charge (B) High intensity Grade. A			
			warranty for 7 years for the retro			
			reflective sheeting from original			
			manufacturer and certified copy of three			
			years outdoor exposure test report from			
			third party test lab for the product offered			
			shall be submitted by contractor.(B)			
			Class-B type-4 retro reflective sheeting.			



10	260020	E	Providing and fiving Courtingons Circ	1336 01	Noc	25064
18	26092B	6	Providing and fixing Cautionary Sign Board made out of 2mm aluminium sheet/ 4 mm ACP (aluminium composite panel), size 90 x 90 x 90 cms equilateral triangle, as per the design of IRC-67- 2012. Pre treated with phosphating process and acid etching coated with one coat of epoxy primer and two coats of best quality epoxy paint, refloctrorized with high intensity prismatic grade retro reflective sheeting of type-4 as per ASTM D-4956 and as per the latest M.O.S.T. specification, 3.6 Mt. long stand post and frame fabricated from suitable size iron angle of 75 x 75 x 6mm / 65 NB circular MS pipe as required and frame fabricated from suitable size iron angle of 35 x 35 x 3mm; painted with best quality epoxy coating in black and white bends. The details of symbol for each board shall be as per the instruction of engineer in charge. The fixing at site shall be in 1:2:4 CC block of size 45 x 45 x 60 cms for each leg, including excavation curing etc. complete under the supervision of Engineer-In- Charge (B) High intensity Grade. A warranty for 7 years for the retro reflective sheeting from original manufacturer and certified copy of three years outdoor exposure test report from third party test lab for the product offered shall be submitted by contractor.(B) Class-B type-4 retro reflective sheeting.	4326.84	Nos.	25961
19	26048	1	Providing & fixing ordinary Kilometre stone of precast C.C. 1:2:4 including necessary reinforcement as per I.R.C. type design in C.C. 1:4:8 including letter & paints etc. complete (For N.H., S.H. & M.D.R.).	841.73	Each	842
20	27101A	2	Providing and fixing marble slab including engraving and painting complete. (A) size 75 cm x 60 cm x 4 cm	955.46	Nos.	1911
21	26163	710	Supplying and fixing cat eye (Stimsonite) made out from Acrylo butyle styrene high compression injection moulding with	375.72	Each	266761



			reflector made of MMC (prismatic type of size 12cm x 6cm x 2.5cm) provided with bituminous adhesive 100g. with each unit for fixing. (High Intensity grade)			
22	14023	1404	Providing and fixing pre-cast concrete kerb stone of gray cement based concrete block 30cm length,30cm height and 15cm thick of M250 grade concrete as per approved design and including excavation for fixing in proper line and level, filling the joint with C:M 1:3 (1cement:3 fine sand) etc complete.	242.55	RMT	340540
23	USSOR 191050		Conducting in situ full size Plate Load Test (PLT) at selected location as per IS :1888 including making loading arrangements & casting of RCC/cast in situ concrete footing as per codal provisions including excavation and refilling of trial pit.			
	191052	4	b. Plate size 45cm x 45cm	10453.50	Each	41814
24	USSOR 192110		Lateral Load Testing of single pile in accordance with "IS Code of practice IS: 2911 (Part IV) for determining safe allowable lateral load of pile" with all labour, material, tool & plants, equipment, machinery, etc. complete as per drawing and specification as directed by the engineer.			
	192111	6	Piles with lateral load capacity of up to 10 ton	174625.72	Each	1047754
	192112	6	Piles with lateral load capacity of above 10 ton & up to 20 ton	58702.21	Each	352213
25	19032	14492	Applying two coats of Birla (white cement based) or Asian (acrylic lapy- putty) or equivalent & two coats of primer of approved brand and manufacture on new concrete surface to give an even shade including thoroughly brushing the surface free from mortar dropping and other foreign matter and sand papered smooth.	47.89	Sqm	694022



26	19031	14492	Finishing concrete surface with weather proof exterior emulsion paint on concrete surface (two coats) to give an required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered materials. etc complete.	44.59	Sqm	646198
			TOTAL AMOUNT OF SCHEDULE - A			48925418



Schedule- B Schedule of Approximate quantities Amount Total Sr. ltem Item of work Unit Rate in No. No. Qty. Rs. Marking out the centre line of the bridge 30300 30300 1 State 1 LS NS/1 and various other components structures and complete lining out and levelling with Total Station, theodolite, level including construction necessary masonry pillars for lines and levels and establishing necessary benchmark etc. complete as directed. 2 State 9137 Earth work for embankment including 240.38 Cu.m. 2196352 breaking clods dressing With all lead and NS/2lift and including watering, rolling, and consolidation of subgrade in layers at O.MC. to required dry density including filling the depressing which occur during the process using vibratory roller 8.T. to 10 T Providing & filling in foundation with 3 1592 2980.51 Cu.m. 4744972 State NS/3 ordinary cement concrete M 15 mix and providing necessary vertical pin headers including formwork vibrating ramming & curing complete. 6118 Providing and laying controlled cement 4527.83 27701264 4 State Cu.m. concrete M 35 for R.C.C. bored piles of NS/41.20M dia. including ramming, vibrating and finishing excluding cost of T.M.T reinforcement etc. complete. 5 174 Conducting Pile low strain integrity test as 1453.39 Nos. 252890 State per ASTM D 5882- 96 code of American NS/5 Society for Testing on cast -in situ RCC pile of 1200 mm diameter inclusive of analysis with all contractor's equipment, manpower, site preparation, lead and lifts etc. complete as per standard procedure, and as directed by the Engineer in charge. Note:- Rate is inclusive All equipment, All labour and consumable required & Mobilization of equipment.



6	State NS/6	2478	Providing and casting in situ controlled cement concrete M-35 for R.C.C. pile cap including necessary formwork, vibrating, curing and finishing complete.	4064.24	Cu.m.	10071187
7	State NS/7		Providing and casting in situ controlled cement M-35 for R.C.C. work For Piers/Abutments as per drawing including centring shuttering scaffolding where necessary laying vibrating curing and finishing complete. Exposed concrete finish and form mark as directed by Engineer-in-charge, etc. complete as per specification.			
	A	3148	0.0M TO 5.0M	4118.78	Cu.m.	12965919
	В	672	Above 5.0M	4338.96	Cu.m.	2915781
8	State NS/8	1202	Providing and casting in situ controlled cement concrete M-35 for R.C.C. work in pier cap, abutment cap, Seismic arrester and dirt wall including controlled cement concrete M-40 bed blocks or pedestals of required size below bearings as per detailed drawings, centring, shuttering, scaffolding, wherever necessary, laying vibrating, curing and finishing complete.	4436.93	Cu.m.	5333190
9	State NS/9		Providing and casting in situ controlled cement M 40 for R.C.C. work in superstructure including centring shuttering scaffolding, ramming, vibrating curing and finishing complete.			
		125	Running line (Fixed shuttering shall be provided as per approved design of fixed shuttering) Note: Cost of fixed shuttering will be paid separately under relevant item.	4387.44	Cu.m	548430
		368	Non running line	5024.75	Cu.m	1849108
10	State NS/10	3360	Providing and casting in situ controlled cement M 35 for R.C.C. work in superstructure including centring shuttering scaffolding, ramming, vibrating curing and finishing complete	4934.86	Cu.m	16581130
	1			1		L



11	Stata	437	Providing and casting in situ controlled	4837.90	Cu.m.	2114162
11	State NS/11	437	Providing and casting in situ controlled cement concrete M 40 Wearing coat having 75mm avg. thickness as per drawing and laid as directed including tamping vibrating finishing curing and filling in joints with bitumen complete.	4837.90	cu.m.	2114102
12	State NS/12	1528	Provision of Reinforced cement concrete crash barrier at the edges of the road, approaches to bridge structures and medians, constructed with M-40 grade concrete with, 450 mm long at expansion joints filled with pre-moulded asphalt filler board, keyed to the structure on which it is built and installed as per design given in the enclosure to MOST circular No. RW/NH - 33022/1/94-DO III dated 24 June 1994 as per dimensions in the approved drawing and at locations directed by the Engineer, all as specified as per drawing attached excluding steel FE 500 D.	1413.60	RMT	2159981
13	State NS/13		Providing and Laying only with Knitted and PVC coated Polyester Uniaxial Geogrid-Techgrid indigenously manufactured from selected high tenacity polyester yarn with high molecular weight (> 25000 g/mol), and low carboxyl end group (<30mmol/kg) for Reinforced soil wall with granular fill of PHi-30 degree (design is to be carried out in accordance with BS-8006 / FHWA) with concrete Panel (M35) as facia, casting & erection of panels with Techgrid, providing & laying of levelling pad of M15, providing and laying coping beam (M25), providing and laying drainage composite TDC-55130 etc. completed as per the necessary drawing and instruction of Engineer In Charge. Excluding providing, laying and compacting selected backfill and retained fill behind the wall, excavation and ground improvement, if any.			
	А	657	1 TO 4 m.	4062.22	Sq.m.	2668879
	В	1405	4 TO 6 m.	4118.78	Sq.m.	5786886
	С	2690	6 TO 8 m.	4362.19	Sq.m.	11734291



	D	2588	8 TO 10 m.	4647.01	Sq.m.	12026462
	E	400	10 TO 12 m.	4996.47	Sq.m.	1998588
14	State NS/14	39481	Providing Earth fill / Sand & filling in approach portion of RE/Retaining Wall as per MORTH section 3100 and IRC:SP:102 latest Revision including laying as per specification ,compaction in 250 mm thick loose layers and dressing (MORTH specification CI. by mechanical means using motor grader including 305.3.5), watering upto required OMC including rolling with the use of vibratory roller when fill is at suitable moisture content with desired field density all as per the approved design ,drawing, specification and directed by the Engineer.	613.07	Cu.m.	24204617
15	State NS/15	1140	Provision of an Reinforced cement concrete crash barrier with friction slab at the edges of the road, approaches to bridge structures and medians, constructed with M-40 grade concrete, 450mm long at expansion joints filled with pre-moulded asphalt filler board, keyed to the structure on which it is built and installed as per design given in the enclosure to MOST circular No. RW/NH - 33022/1/94-DO III dated 24 June 1994 as per dimensions in the approved drawing and at locations directed by the Engineer, all as specified with friction slab as per drawing attached excluding cost of steel FE 500 D.	4738.92	RMT	5402369
16	State NS/16	4832	Construction of 200 mm thick compacted coarsed granular subbase (Grade-I crushed B.T materials of 53 mm to 26.5 mm @ 35 %,26.5 mm to 4.75 mm @ 45%, Below 2.36 mm @ 20 %) by providing close graded material , mixing in a mechanical mix plant at OMC, carriage of a mix material to work site, spreading uniform layers with motor grader on prepared surface and compacting with vibratory power roller to achieve desire	1345.32	Cu.m.	6500586



			density, complete clause as per 401.			
			density, complete clause as per 401.			
17	State NS/17	6040	Providing and laying wet mix base course macadam 250 mm in Two layer using machine crushed chips as per required gradation mixing with required optimum quantity of water conveying the mix to site and spreading to grade and camber with mechanical paver consolidation by vibratory roller including material, labour, plant and machinery and equipment etc. complete.	1426.12	Cu.m.	8613765
18	State NS/18	1610	Providing and laying wet mix base course macadam 150 mm in Two layer using machine crushed chips as per required gradation mixing with required optimum quantity of water conveying the mix to site and spreading to grade and camber with mechanical paver consolidation by vibratory roller including material, labour, plant and machinery and equipment etc. complete.	1426.12	Cu.m.	2296053
19	State NS/19	7104	Providing and laying 90 mm DBM in single layer using crushed stone aggregate BT chips as per required gradation and using emulsion asphalt as a tack coat @ 2.5 kg / 10 sqmt and the VG-30 grade asphalt at 40 kg/MT)by total weight of mix hot laid process using hot mix plant including heating and mixing asphalt & materials by hot mix process transporting the mix and laying by paver finisher including consolidation with vibratory roller including cost of material, labour, machinery equipment and fuel , oil , lubricant for plant and machinery using contractor's own plant and machineries etc. complete.	2326.93	M.T.	16530511

	NS/23		concrete M-40 as per detailed drawings with necessary reinforcement including, shuttering, laying vibrating and finishing			
23	State	250	Providing parapet of controlled cement	876.68	RMT	219170
22	State NS/22	18	Providing and casting in situ controlled cement concrete M-35 for approach slab including formwork curing and finishing	4229.88	Cu.m.	76138
21	State NS/21	34891	Providing and applying priming coat with emulsion SS1 grade at the rate of 7.50 kg/ 10 Sq.mt. including cost of asphalt and preparing the surface heating, and applying etc. complete.	40.80	Sq.m	1423553
20	State NS/20	2430	Providing and laying 30 mm Bitumen concrete using crushed stone aggregate BT chips as per required gradation and the VG-30 grade asphalt at 54 kg/MT)by total weight of mix hot laid process using hot mix plant including heating and mixing asphalt & materials by hot mix process transporting the mix and laying by paver finisher including consolidation with vibratory roller including cost of material, labour, machinery equipment and fuel, oil, lubricant for plant and machinery using contractor's own plant and machineries etc. complete.	2767.40	M.T	6724782

					S	<u>chedule- C</u>			
	Schedule of Approximate quantities								
Sr. No.	ltem No.	Total Qty.	Item of work	Rate	UNIT	Amount in Rs.			
1	NS/1	187	Providing Steel Liner 6 mm thick for pile including Fabricating and Setting out as per Detailed Drawing.	65280	MT	12207360			
2	NS/2	3081	Providing and fixing in position steel Fe 500 D bar reinforcement For R.C.C. bored piles, Pile Cap, pier, Abutment, Abutment cap, pier cap, Pedestal & seismic arrester, Super Structure, Approach slab, crash barrier, friction slab, wearing coat etc. any structure of steel grade FE-500 D (TMT) including cutting, bending, hooking, tying, welding etc., complete as per detailed drawing and specification.	69117	MT	212949477			
			TOTAL AMOUNT OF SCHEDULE -C		225	156837			

	<u>Schedule- D</u>								
	Schedule of Approximate quantities								
Sr. No.	ltem No.	Item of work	UNIT	Quantity	Rate	Amount in Rs.			
1	1	Misc. State SOR /USSOR of W.Rly. items requiring for successful completion of the work as advised by in-charge of the work.	LS	1	1500000	1500000			
2	USSOR 33062	OPC 53 Grade USSOR of W.Rly. items for supply of cement as and when required as per instruction given by in-charge.	Tonne	20	4830	96600			
	TOTAL AMOUNT OF SCHEDULE-D				1	596600			

					Scl	nedule- E
		Schedule of Approximate	e quan	tities		
Sr. No.	ltem No.	Description	UNIT	Total Quantity	Rate	Amount in Rs.
1	NS/1	Supply & Fabrication of steel girder spans including its components (Stiffeners, Bracings, Splices, Studs etc.) as per the approved drawings for composite construction of superstructure of the Road Over Bridge with contractor's own Steel confirming to IS: 2062-2011 Grade E- 250 (B0) with all welds, HSFG Bolts, nuts bolts, rivets etc. with contractor's own materials, fabrication, machinery, templates, fixtures, equipments tools and plants transportation, skilled/unskilled labour, excise duty., Octroi, sales tax and other taxes, all leads lifts, descent, loading, unloading, crossing one or more Railway track if required etc. complete and as per technical specifications. The rate is inclusive of transportation of fabricated girder parts to site by contractor's own means at his cost. The rate shall also be inclusive of cold straightening of deformed and bent girder parts before their assembly. Work has to be done as per drawings and specifications approved by Railway.	MT	692	105390	72929880
		High quality superior brand of paint should only be used. For Painting prior approval for superior brand / make of the paint should be taken from engineer in charge.				
		Note:1. The fabrication of girders must be got done from RDSO approved firms only.				
		2. The rate is inclusive of assembly of girder with service bolts as per approved drawing in shop for checking by Engineer's representative and dismantling the same after checking for transportation to the site.				

		3. Weight of HSFG bolts, Rivets, Welds shall not be considered for payment. Nominal weight of the girder spans including its components (Stiffeners, Bracings, Splices, Studs etc.) as per drawing will only be considered for payment				
2	NS/2	Metalising girder/girder components such as cross girders, top chord channels, bracing etc. of Steel Girder as directed by Engineer with aluminium spray not less than two layers after preparing surface by sand/grit blasting as per provision laid in Appendix VI of IRS B 1179 code (latest alteration) including one coat wash primer (IS-5666) one coat zinc crome primer (IS-104) and two coats of aluminium paint (IS-2339) with approved paint conforming to IS specification for fabrication & erection of steel girder bridge (RS B 1-79) as corrected up to date with contractor's own materials, tools, plants labour, loading/unloading, transportation, handling, re-handling if any including all lead, lifts descents, crossing of track/obstruction etc. complete in all respect and as per direction of the Engineer.	Per Sq.m.	12000	664	7968000
3	NS/3	Assembling, Welding, Erecting, Bolting by HSFG bolts, Riveting if any as per approved drawings and Launching of girder spans including its components on running line / Non- Running line /Running electrified line / under block period with the help of road crane of required capacity as per Railway's approved drawings & Scheme with other ancillary steel structures fixed to the girder, where necessary, in proper level and alignment and as per technical specifications. The rate shall be inclusive of supply, erection and dismantling of staging and scaffolding and other temporary arrangements required for the purpose of assembly, erection and launching of girders. The rate shall also be inclusive of cold straightening of deformed and bent girder parts before/after their assembly. Work has to be done as per drawings and specifications approved by Railway.				



		Note: Weight of HSFG bolts, Rivets, Welds shall not be considered for payment. Nominal weight of the girder spans including its components (Stiffeners, Bracings, Splices, Studs etc.) as per drawing will only be considered for payment.				
	(a)	Launching of Steel girder spans including its components on running line /Running electrified line / under block period with the help of road crane of required capacity as per Railway's approved drawings with other ancillary steel structures fixed to the girder where necessary in proper level and alignment and as per technical specifications.	MT	239	19305	4613895
	(b)	Launching of Steel girder spans including its components on non-running line with the help of road crane of required capacity as per Railway's approved drawings with other ancillary steel structures fixed to the girder where necessary in proper level and alignment and as per technical specifications.	MT	453	5687	2576211
4	NS/4	Fabricating, supplying and erecting in position standard structural steel sections manufactured from IS approved manufacturers only ,conforming to IS :2062 - 1992 (including latest amendments) including welding with approved quality welding rods, supply and fixing of correct size turn bolts including one primer coat of red lead paint conforming to IS:102 or Zinc chromate paint conforming to IS:104 followed by tow coats of Aluminium paint as per IS : 2339 with all contractor's materials, labour, tools and plants etc in bolted/welded construction as directed by Engineer in charge. Work shall be carried out as per IS:800-1984 (with latest amendments), IRS specification No. B3-61 part 2 and IS 816 for welding.	MT	45	72809	3276405

5	NS/5	Providing and fixing in position true to line and level POT cum PTFE bearings including cost of all materials, fixtures, preparing surface for receiving bearing, grouting of sleeves with non-shrink high strength grout, loads testing of bearing, transporting and fixing in position including all lead and lifts etc. complete as per approved design &				
		drawing and as directed by Engineer-in- charge under girders as per approved drawings and special condition specification of contract. The contractor will supply design & drawing for this item.				
	NS/5 a	Fixed bearing	MT	1413	362.00	511506
	NS/5b	Sliding bearing	MT	6088	527.00	3208376
		Note: The rate is for finished item complete and paid only after fixing in position below the girder.				
6	NS/6	Load testing of one composite steel/span designing and load testing of one composite girder/span as selected by the engineer conforming to Rly. Standard's with loads to be applied and removed incrementally etc. complete as per special condition and specification of contract, as per relevant IS/IRC codes with contractors labour supervisor, T&P's all taxes, equipment, leading materials instruction of load test jacks etc., dial gauges, including all lead & lift.	Each	1	283041.95	283042
		TOTAL AMOUNT OF SCHEDULE- E				95367315

					Sc	hedule- F
		Schedule of Approximate	quantiti	es		
Sr. No.	ltem No.	Description	UNIT	Total Quantity	Rate	Amount in Rs.
1	NS/1	Epoxy painting. Supplying and applying epoxy paint of approved quality on surfaces of abutment, abutment caps, returns, piers, pier caps, PSC girders/slabs, deck slab, parapet walls, crash barriers etc. confirming to the specifications laid down in the special conditions of contract. The rate inclusive of contractor's own paint, material, equipments, machineries, labour, taxes, with all lead, lift, scaffolding staging, etc. complete. (Rates are for finished item and will be paid after application as per specification.)	sqm	3055	265	809575
2	NS/2	Providing & fixing Safety Screen as per RDSO Drg. No. EL / C / 0068 MOD " E " , on the Parapet with necessary fixtures etc. as per detailed drawing including contractor's own materials, labours, tools and plants, etc. complete.	sqm	374	1122	419628
3	NS/3	Providing, fixing and maintaining MS fabricated traffic barricading of 2.50m height on either side of the carriage way / portion of the carriage way closed to the traffic including provision of all sign boards/ bollards and warning lights etc. as per the Engineer in charge.	Metre	2167	315	682605
4	NS/4	Designing and preparation of detailed drawing of foundation, substructure, super structure staircase, retaining wall, bearings, temporary arrangements, launching scheme etc. as per relevant IR,BIS,IRC and other codes, preparation of fabrication drawings, Proof checking of designs and drawings from IIT, Approval of design and drawing from respective authority, approval, to carry out any addition/ alteration/ modification /change in drawing during design approval and	Job work	1	1290000	1290000



· · · · · ·		exection of the training the terms of	-			1
		construction phase at work, providing guidance during construction and site visit				
		if any.				
		The Rate inclusive of following items:				
		, , , , , , , , , , , , , , , , , , ,				
		i) Preparation of preliminary and detailed design of foundation, substructure, superstructure, including staircase, approach slab (wherever applicable) and all other drawing as required for construction of DFC + Railway portion of the ROB and both approaches.				
		ii) Submission of proof checked detailed design for Foundation, Sub-structure, Super-Structure (if in non-RDSO span is adopted), Reinforced Earth Wall and Retaining wall.				
		iii) The detail design of superstructure will be further governed as per para (iv) h of deliverables in part-l Chapter-III.				
		iv) Out-station visits (Sites, District HQs, WR HQ, Delhi/NCR and other locations in ADI-PNU section, with stakeholders will be attended by consultant team on specific advise of DFCCIL and nothing extra will be paid for visits for such meetings during currency of contract.				
		v) Proof Checking of design of ROB structures of Railway portion from IIT, and there after approval of same by WRIy and/ or DFCCIL.				
		vi) Proof Checking of design of ROB structures of approaches from IIT and Approval of GADs, detailed design and drawing of viaducts as well as RE wall and retaining walls of approaches of said ROB from respective state Govt authorities.				
5	NS/5	Making and fixing of check rails of 52 kg/ 60 kg rails of various lengths for level crossing as per approval drawings.	Each LC	4	2850	11400
6	NS/6	Providing, arranging, managing and maintaining 500 sq.ft. well-furnished AC office and well equipped Laboratory with 3 tables, 10 chairs, 2 steel almirah, one computer with printer & operator, sufficient	Per month	20	15900	318000



Total of Schedule A, B, C, D, E & F	Rs. 57,02,48,693
TOTAL AMOUNT OF SCHEDULE-F	3531208
number of display etc. to the satisfaction of the Project Manager including Electrical, Water expenses etc. For execution of this item the date of start shall be considered only when the Contractor has actually rented/constructed the required premises established the office & Laboratory as per requirement. This item shall remain valid only for original contact period; no additional payment shall be made for whatsoever reason even if time extension if provided or date of completion is extended. This office and laboratory including furniture and all other equipment shall be property of contractor after completion of Project.	

END OF TENDER DOCUMENTS

