

E-Tender No. MUM/N/EN/Major/Important Bridges/Package-IV, date 18.07.2019

For

Construction of Major / Important Bridge No. 92 & 93 (Balance Work) between Vaitarna - Saphale Railway station of Virar – Surat Section of Mumbai Division of Western Railway in connection with Western Dedicated Freight Corridor.

FINANCIAL BID (PACKET-B)

TENDER DOCUMENT July 2019

Employer:
DEDICATED FREIGHT CORRIDOR CORPORATION OF INDIA LIMITED
CGM/NORTH/MUMBAI UNIT
(A GOVERNMENT OF INDIA ENTERPRISE)
Under
MINISTRY OF RAILWAYS

FORM No. 3

SUMMARY OF PRICES

Name of work:- Construction of Major / Important Bridge No. 92 & 93 (Balance Work) between Vaitarna - Saphale Railway station of Virar – Surat Section of Mumbai Division of Western Railway in connection with Western Dedicated Freight Corridor.

SI. No.	Description of works	Cost as per Schedules	Rates to be quoted in figures & words (Clearly mention above / below / at par on Schedules/Items updated DFCCIL Rate / cost given in column 3)
1	2	3	4
1.	Execution of all works as per Schedule "A"	Rs. 2,89,06,037.00	
2.	Execution of all works as per Schedule "B"	Rs. 52,74,05,800.00	Rates above / below / at par as per
3.	Execution of all works as per Schedule "C"	Rs. 13,49,12,385.00	schedules shall be filled separately in Microsoft Excel File.
4.	Execution of all works as per Schedule "D" (USSOR of Western Railway)	Rs. 50,00,000.00	
	Grand Total	Rs. 69,62,24,222.00	

Notes:

- (i) The above prices are inclusive of all taxes, duties, levies, etc. Except GST.
 - a. GST as applicable from time to time on taxable value of each running account bill shall be paid by DFCCIL.
 - b. The contractor should adhere to anti profiteering provisions as per section 171 of the CGST Act. Where due to change in the rates of GST / Change in law, the contractor gets any credits / benefits, the same shall be passed on to DFCCIL by way of reduction in prices.

- (ii) The tenderer should quote single percentage above / par / below for each schedule.
- (iii) If the uniform percentage quoted by the Tenderer does not clearly indicate whether the rates are above/at par/below the estimated rates then through sign convention it will be considered to be on plus side and evaluated accordingly.
- (iv) Rate of item payable to contractor shall be as per Above / Below / AT par on rates of schedule.

FORM No. 4

SCHEDULE -1 SCHEDULE OF PRICES & TOTAL PRICES

<u>NAME OF WORK</u>:- Construction of Major / Important Bridge No. 92 & 93 (Balance Work) between Vaitarna - Saphale Railway station of Virar – Surat Section of Mumbai Division of Western Railway in connection with Western Dedicated Freight Corridor.

Schedule- A

Schedule of Approximate quantities

Item No.	Total Qty.	Item of work	Rate	UNIT	Amount in Rs.
192010		Earth work in excavation for foundations and floors of the bridges, retaining walls etc., including setting out, dressing of sides, ramming of bottom, getting out the excavated material, back filling in layers with approved material and consolidation of the layers by ramming and watering etc. incl. all lift, disposal of surplus soil upto a lead of 300 M, all types of shoring and strutting with all labour and material complete as per drawing and technical specification as directed by Engineer in charge.			
192011	448	All kinds of soils	437.53	Cum	196013.00
192012	163	Ordinary Rock	451.19	Cum	73544.00
192100		Conducting load testing of a single pile Up to following capacity in accordance with IS 2911 (Part IV) including installation of loading			

		platform and preparation of pile head or construction of test cap and dismantling of test cap after test etc. with all labour, material, tool & plants, equipment, machinery, etc complete as per drawing and specification, as directed by the Engineer.			
192107	6	Initial and Routine Load Test above 100 ton capacity Up to 250 ton capacity pile.	1,99,648.0	Each	1197888.00
192104	42	Extra for every increase of 50T in pile capacity or part thereof over 250 T	57,181.95	Each	2401642.00
201040	5978228	Design, manufacturing, Supplying and fixing in position elastomeric bearing pads under prestressed concrete girder, for Pre-cast as well as cast- in-situ girders as per approved drawing. The rate shall include cost of load test of one No. bearing from DFCCIL approved firms and all fixing materials, equipment's, machineries, labour, taxes, loading, unloading, leading, lifting, etc. complete. Rates include getting the drawing approved from DFCCIL and cost of inspection during manufacturing from DFCCIL approved organization. (Note. 1.The rate is for finished item complete and paid only n after fixing in position below the girder. 2.The volume shall be given in the drawing and no deduction shall be made for inserted steel plates etc.)	1.51	Cucm	9027124.00

		T			
201060		Load testing of one or more spans of bridge as selected by the engineer as per approved load test procedure following relevant IS/IRC/Railway codes with contractor's labour, deflection measuring instruments, loading materials, recoding and analysing the load testing results including all			
		lead & lift, etc. complete as required. The rates are all inclusive and will be paid after load test is finished and girder is cleared of the kentleadges / loading material etc. The load shall be 1.25 times the stipulated design load Based on Design load & not span.			
201061	2	For spans Design Load up to 100MT	1,11,966.21	Each	223932.00
		To span a colon ap to com			
201062	10	Extra for every increase of 100 MT or part thereof in the span load capacity's up to 800 MT	1,09,078.70	Each	1090787.00
201050		Providing and fixing in position of standard performed sealed and slab type or strip seal elastomeric type expansion joints for Railway bridges or Road Over Bridges as per approved drawings and latest MOST/IRC specifications. The rates are inclusive of supplying, fixing with contractors' own materials e.g. inserts, bolts, socket tubes, Neoprene sheet/cap etc. equipment's, machineries, labour all taxes, royalty, all lead & lifts, transport, testing surface preparations complete.			

201051	322	For 80 mm Expansion	14,301.53	RMT	4605093.00
221060	138	Providing and laying pitching with stone boulders weighing not less than 35 kg each with the voids filled with cement sand mortar 1:4 on slopes laid over	2,132.51	Cum	294286.00
222140	97	Providing cutting, fabricating, treating, fixing, fixing & painting Galvanised iron structural steel confirming to IS in access ladders, inspection, platforms, Trolley refugee, railing etc. joints welded to neat finish incl. one coat of primer & two coats of synthetic enamel paints.	97,595.53	MT	9466766.00
222150	49	Providing /fixing/leaving/grouting various size GI-HTS bolts/holding down bolts in concrete column or in other structural steel member with proper nuts bolts, washers/plates as a complete job. Note-Cement used in grouting will be paid separately under relevant item.	155.06	Kg	7598.00
222230	8	Painting the HFL and danger level marks, year of HFL on bridge abutments and piers with ready mixed plant as per standard in two coats over one coat of primer with all materials, labour, tolls, scaffolding, all lead and lift etc including writing complete.	165.49	Each	1324.00
222240	8	Providing cast in situ bridge number plaques as per Railway drawing in cement concrete 1:2:4 mix using 20 mm hard stone	1,129.83	Each	9039.00

		aggregate embedded in 30mm notch in bridge parapet coping duly engraving the letter and figures and an arrow indicating the direction of flow and finishing the top exposed surface with cement mortar 1:3, painting letters and figures with two coats of black enamel paint on two coats of white back ground with all labour, tools, cement, paints etc. with all lead and lifts			
222250	8	Providing cast in situ plaques for bridge foundations details of size 45x45x5 cm in cement concrete 1;2;4 mix using 20mm hard stone aggregate embedded in 30mm deep notch over abutment & piers, engraving the letters & figures with CM 1:3 and finished smooth including painting letters and figures with 2 coats of black enamel and plaque with white enamel with all labour, tools, cement, paint, curing etc. as a complete job	1,263.91	Each	10,111.00
242010	200	Providing 1.2m high fencing with 1.8m R.C.C post placed every 3 m apart, embedded in cement concrete blocks, every 15th post (or nearer if there is abrupt change of ground slope), last but one end post and corner post shall be strutted on both sides and end post one side only, and struts embedded in cement concrete blocks, provided with 5 horizontal lines and two diagonals of G.I	63.41	Mete r	12682.00

		Total of Schedule "A"		Rs.2,	89,06,037.00
		concrete @ 0.80 kg/sqm with pot life not less than 60-90 minutes and as per specifications including cleaning the surface.			
222120	30	Providing & applying Epoxy for bonding of new concrete to old	738.58	Sqm	22157.00
181030	18	Demolishing R.C.C. work including cutting and stacking of steel bars and disposal of unserviceable material within 50m lead.	1,178.53	Cum	21,214.00
014052	20	Turfing with planted doob grass	7601.63	100 Sqm	152033.00
014050		Turfing / planting, including all lead and lift, and watering as required until properly rooted, with. Note - Initially payment of only 40% will be made. Balance 60% will be paid only after 3 months of maintenance period if the turfing is properly rooted.			
241012	66	Precast R.C.C standard struts 2.0 meters long	636.50	Each	42009.00
241011	66	Precast R.C.C standard post (for barbed wire fencing) 1.8m long	769.57	Each	50,792.00
241010		Supplying at site			
		the post (cost of post, struts and concrete to be paid for separately)			
		(min) between the two posts fitted and fixed with G.I. staples on turn buckles or G.I. binding wire tied to 6 mm bar nibs fixed while casting			
		barbed wire 9.38kg per 100 meters			

				Schedule -				
Schedule of Approximate quantities								
SN Tota		Rate	UNIT	Amount in Rs.				
1.	Casting at site or pre casting in casting yard and providing M-50 Grade pre stressed post tensioned concrete Girders (U Girder, Box Girder, Voided Slab & I- Girder etc.) & RCC slab including deck slab, Diaphragm, wearing coat etc. In bridge super structure, as per approved design and drawing and or as directed by the Engineer in charge. The rate includes cost of Cement, all types of steel (SAIL/RINL /TISCO/ESSAR/JINDAL only), all lead, lift, transportation, loading, unloading, handling all materials, labours, equipment's, casting bed, launching of girders, tools & plants, fuel, oil & lubricants etc., complete including crossing of running track etc. to obtain required finished product, following the relevant specifications, approved design and drawing and or as directed by Engineer in charge, required for execution of following activities which are parts of this item; 1) Providing and fixing of centring shuttering in required profile and level and design, 2) Providing, cutting, bending,							

wires) and fixing in position Thermo mechanically Treated (TMT) Fe 500 D reinforcing bars (confirming to IS 1786) of various diameters,

- 3) Providing and applying (mechanically sprayed) cement polymer composite coating (CPCC) of approved quality (confirming CECRI) without hindrance the prevailing property of bond strength, on thoroughly cleared by abrasive cleaning of surface of all the embedded reinforcement bars to protect the un tensioned reinforcement steel bars to protect from corrosive action by alkaline environment present in the surround concrete, before sufficient time of their placement, including cleaning of surface from mil scales, dust, rust oily products if any etc. complete as directed by the Engineer in charge.
- 4) Providing, fabricating & fixing in position to exact design profile, prestressing H.T.S. cables of all classification made from Low Relaxation strands conforming to IS 14268-1995 in pre-stressed concrete girders / slabs etc. including supplying, cutting, making into cable with necessary spacers, colour coding, protecting with water soluble oil at all time, anchoring of cable, supplying placing CORRUGATED HDPE and SHEATHING DUCTS conforming to IS 1343-2012 of required diameter / thickness, vent pipe, placing, bending, routing, fixing, stressing and grouting

		of cable ducts with cement grout, anchorage sets in required number with provision for future prestressing, if any. Note a. 50 % payment will be released after casting of Girder. b. 20 % payment will be released after prestressing of Girder. c. Balance 30 % payment will be released after final placement of Girder at site.			
	874	For superstructures having spans of greater than 16 m but less than or equal to 24 m (excluding PSC U Girders).	2,56,285.74	RM of Single track	223993737
2	4425	Providing and installing Bored cast in situ Reinforced cement concrete piles of specified diameter and length below pile cap, using M-40 grade Design Mix Cement Concrete (using 20 mm graded crushed stone aggregate and coarse sand of approved quality), to carry a safe working load not less than specified, including the cost of providing and laying steel liner of 1.2m dia, Reinforcement, CPCC, fabrication and lowering of reinforcement cage, Mixing of concrete by batching plant, transportation of concrete, placing of concrete using tremie pipe, chipping off of pile top to remove laitance concrete above cut off level etc, pumping and balling out water.	43,001.90	RM	190283408

The rate includes cost of Cement, all (SAIL/RINL types of steel /TISCO/ESSAR/JINDAL only), Empty boring, all lead, lift, transportation, loading, unloading, handling materials, labours, equipment, tools & plants, fuel, oil, lubricants, Bentonite /Polymer, Chipping, Geotechnical report etc. complete including crossing of running track etc. to obtain required finished product, following the relevant specifications, approved design and drawing and or as directed by Engineer in charge) for all activities of the item.

- 1) Providing, fabricating and installing of MS for board piles for all diameters with specified thickness (bottom most liner 8 mm thick plate and remaining 6 mm thick plate) of steel plate, compete up to refusal or the level as specified in design and /or directed by the Engineer in charge). The rate includes cost of welding, electrodes and power supply etc. Before installation the external surface of liner shall be protected from corrosion by applying 2 coats black paint, having total coat thickness of 150 micron.
- 2) Providing, cutting, bending hooking, binding (with soft 16 SWG GI wires), lowering and fixing in position Thermo mechanically Treated (TMT) Fe 500 D reinforcing bars (confirming to IS 1786) of varies diameters,
- 3) Providing and applying

	(mechanically sprayed) Cement Polymer Composite Coating (CPCC) of approved quality (Confirming to CECRI) without hindrance the prevailing property of bond strength, on thoroughly cleaned by abrasive cleaning of surface of all the		
	embedded reinforcement bars to protect the un tensioned reinforcement steel bars to protect from corrosive action by alkaline environment present in the surround concrete, before sufficient time of their placement, including cleaning of surface from mil scales, dust, rust and oily products in any etc. complete as directed by the Engineer in charge.		
3	Constructing the pile caps over the pile groups under piers/abutments, using M-40 Grade Design mixed Reinforced Cement Concrete, of shape, size and levels as mentioned in the approved drawing and or as directed by Engineer in charge. (measured as one pile cap supporting twin track superstructure).		
	The rate includes cost of Cement, Reinforcement steel (SAIL/RINL/TISCO/ESSAR/JINDAL only), all lead, lift transportation, loading, unloading handing of all materials, labours, equipment's, tools & plant, fuel, oil & lubricants etc., complete including crossing of running track etc., to obtain required finished product, following the relevant specification, approved design and drawing and or as directed by Engineer in charge)		

required for the execution of following activities which are parts of this item:

- 1) Earth work in excavation all kind of soil/soft rock/hard rock as per approved drawings and dumping site or spoil heap, within railway land, including lead and lift, any incidental work, during excavation, soring, complete.
- 2) Dewatering of natural or accumulated water from any location of foundation pit.
- 3) Providing and laying in situ machine mixed M-15 grade concrete, for Levelling course below pile caps, including shuttering, mixing in mechanised batch mix plant, compacting, curing etc. complete true to level and position and/or as directed by Engineer and as per specification. No extra payment shall be paid.
- 4) Providing and fixing of centring, shuttering in required profile, level, shape and size as approved drawing, and/or as directed by Engineer and as per specification.
- 5) Providing, cutting, bending, hooking, binding (with soft 16 SWF GI wires) and fixing in position Thermo mechanically Treated (TMT) Fe 500 D reinforcing bars (confirming to IS 1786) of various diameters,
- 6) Providing and applying

	(mechanically sprayed) Cement Polymer Composite Coating (CPCC) of approved quality (Confirming to CECRI) without hindrance the prevailing property of bond strength, on thoroughly cleaned by abrasive cleaning of surface of all the embedded reinforcement bars to protect the un tensioned reinforcement steel bars to protect from corrosive action by alkaline environment present in the surround concrete, before sufficient time of their placement, including cleaning of surface from mil scales, dust, rust and			
20	For spans greater than 16 m but less than or equal to 24 m	56,56,432.74	No.	113128655
	Total Amount of Schedule - B		Rs. 52	,74,05,800.00

Schedule - C

	Schedule of Approximate quantities						
SN	Total Qty.	Item of work	Rate	UNIT	Amount in Rs.		
1	2	Clearing and grubbing site/road/land including uprooting all vegetation, grass, bush shrubs, saplings and trees with girth, removal of stumps of trees of girth of all sizes including removing stumps of trees cut earlier and disposal of unserviceable materials and stacking of serviceable materials as directed by Engineer with all leads and lifts etc. complete as per specification before commencement and after commencement and after commencement of the work.	27302.00	LS	54604.00		
2	2	Marking of the centre line along longitudinal axis and etc. with total station theodolite including making drawings and providing all soft copies as directed by engineer in charge.	15,512.50	LS	31025.00		
3	0	Providing and laying in situ machine mixed M-15 grade concrete including shuttering, mixing in mechanised batch mix plant, compacting, curing etc. complete true to level and position as directed by Engineer and as per specification. The rate includes all lead, lift, materials (Including Cement), Labour, tools plant, fuel etc.	4157.35	Cum			
4	414	Providing and laying in situ machine M- 15 grade concrete including shuttering mixing in mechanised batch mix plant, compacting, curing etc. complete true to level and position as directed by Engineer and as per specification. The	4854.79	Cum	2009883		

		rate includes all lead, lift, materials (including cement), labour, tools plant, fuel etc.			
4	169	Conducting pile low strain integrity test as per ASTM D 5882 latest version (Code of American Society for testing) or as per IS 14893 on cast-in-situ RCC pile of 1200 mm diameter inclusive of analysis, with all contractor's equipment, manpower, site preparation, lead and lifts etc complete as per standard procedure, and as directed by the Engineer in charge. 1) All equipment 2) All labour and consumable required 3) Mobilisation of equipment, staff etc. 4) Preparation and submission of Reports in 3 copies 5) Site Preparation	1,406.55	Nos.	237707
5	82436	Supplying, laying (not exceeding layers of 30 cm each), spreading, levelling, dressing and compacting (mechanical compaction), the earth in filling in embankment, guide bunds, around buried type abutments, bridge gaps, trolley refuges, rain bunds if provided, platforms etc. with earth excavated from outside railway/DFCC boundary entirely arranged by the contractor at his own cost as per RDSO's guidelines and specifications as per RDSO/2007/GE: 0014 and special condition of contract including all leads, royalty, lifts, ascents, descents, loading, unloading, transportation, crossing of nallahs or any other obstructions. The rates shall include all dressing of bank to final profile,	296.60	Cum	24450518

		demarcation and setting out of profile, benching of existing slope of old bank, all handling/re-handling taxes, octroi and royalty etc. as a complete job. The earth shall be spread in layers not exceeding 30cm, levelled and compacted mechanically, to achieve specified density as per specification, testing as per IS codes incl. cost of water, T&P consumable material and all labour as a complete job. The rates include all material, labours, equipment's, machineries, tools and plants and fuel etc.			
6	5918	Supplying, laying, spreading, levelling (each layer of 30 cm in loose state), dressing and compacting (mechanical compaction), the Subgrade materials, over embankment/cutting, in total depth of 1 m (Compacted Depth) as per RDSO Guide line - RDSO/2007/GE: 0014, specification and special condition of contract including all leads, lifts, ascents, descents, loading, unloading, transportation, crossing of nallahs or any other obstructions. The rates shall include all dressing of bank to final profile, initial site clearance, cutting of shrubs, removal of roots of vegetation growth & heavy grass, surfacing and levelling to give required slope, benching if required on existing bank slope, demarcation and setting out of profile, all handling/re-handling taxes, octroi and royalty etc. as a complete job.	526.18	Cum	3113933

		The earth shall be spread in layers not exceeding 30 cm, levelled and compacted mechanically, to achieve specified density as per specification, testing as per IS codes incl. cost of water T&P consumable material and all labour as a complete job. The rates include all material, labours, equipment's, machineries, tools and plants and fuel etc. 1) No separate payment shall be made for, blending of material (if required). 2) No separate payment shall be made for required testing as per relevant IS specification.			
7	2811	Supplying, laying, spreading, levelling (each layer of 25 cm in loose state), dressing and compacting (mechanical compaction), the Blanket materials, over Subgrade in embankment/cutting, in total depth of 0.6m (Compacted Depth) as per RDSO Guide line - RDSO/2007/GE: 0014, specification and special condition of contract including all leads, royalty, lifts, ascents, descents, loading, unloading, transportation, crossing of nallahs or any other obstructions over embankment/cutting in layers of 30 cm in loose state to make the embankment of designed profile as per specifications. The rate is inclusive of demarcation and setting out of profile, benching if required on existing octroi and royalty etc., using contractors own labour, material, machinery, fuel etc.	1,236.04	Cum	3474508

		The earth shall be spread in layers not exceeding 30 cm, levelled and compacted mechanically, to achieve specified density as per specification, testing as per IS codes incl. cost of water T&P consumable material and all labour as a complete job. 1) No separate payment shall be made for, blending of material (if required). 2) No separate payment shall be made for required testing as per relevant IS specification.			
8	1209	Providing Boulder backing behind Abutment, wing wall, return wall with hand packed boulders & cobbles with smaller size boulders toward the back including all lead, lift, labour & other incidental charges as complete work in all respect.	616.78	Cum	745687
9	90	Supplying, laying, spreading, levelling and compacting the Dry lean concrete, with 20mm to 80mm Coarse Aggregate, sand and cement, in 1m depth (from top to formation) x 4.8 m width ad 6m length, in layers not exceeding 30 cm each, as Transition system, Behind the Abutment, as per RDSO Report GE:R-50, with contractors own, labours, materials, equipment's, machineries, tools, and plants and fuel etc. The rate includes all lead lift, loading, mixing, unloading and transportation. No extra payment shall be made for cement.	2,943.65	Cum	264929
10	341	Supplying, laying, spreading, levelling and compacting 20mm to 80mm Coarse Aggregate, in layers not	1,863.98	Cum	635617

		exceeding 30cm each, as Transition system, Behind the Abutment, as Per RDSO Report GE:R-50, with contractors own, labours, materials, equipment's, machineries, tools and plants and fuel etc. The rate includes all lead lift, loading, mixing, unloading and transportation.			
11	2338	Providing and laying of filter media consisting of granular materials of GW. SP,SW groups as per IS 1498-1970 in required profile behind boulder filling of abutments, wing walls/return walls etc above bed level with labour and material complete job as per drawing and technical specification of RDSO Guidelines.	1,224.87	Cum	2863746
12	188	Providing and laying in situ Design mixed M-25 grade Cement concrete, with 6mm to 20mm Coarse Aggregate, Sand and Cement, in Toe Wall and Drop Wall etc, including shuttering, mixing in mechanised batch mix plant, compacting, curing etc. complete true to level and position as per approved drawing or/and as directed by Engineer and as per specification. The rate includes all lead, lift, materials (including Cement), loading, unloading, transportation, royalty, labours, toolsplant, Machinery and fuel etc.	6,146.67	Cum	1155574
13	476	Providing the masonry steps on approaches to the bridge, rate includes all the material including cement, sand, masonry stone, etc, labour, tools & plants, machinery, lead, lift and transportation etc. complete to obtain	135.27	Nos.	64389

		finished product as per relevant specifications and directions by the Engineer in charge.			
14	8	Fabricating, erecting, supplying and painting, River Name Board, Complete in all respected as approved in Drawing or as directed by Engineer in-charge. The name board shall be fixed in cement concrete at location as specified in the bridge manual, with cost of all material including cement, sand, coarse aggregate etc. labour, lead lift loading, unloading tools & plants machinery and fuel etc. to obtain finished product. Rates inclusive of writing the details, Name of River, Bridge Number & span specified in approved drawing, no extra charge shall be paid for welding electrodes or any fasteners, washers, bolts etc.	11,293.10	Nos.	90345
15	3579	Providing and laying in position machine mixed, machine vibrated and machine batched Design mix cement concrete M 40 Grade (cast -in situ) using 20 mm graded crushed stone aggregate and coarse sand of approved quality in RCC work for various components of Bridges like raft, piers, pier cap, abutment, abutment cap, wing/return walls toe walls, girders, slabs, pedestals, stoppers, trolley refuges, RCC Box etc including finishing using Admixture in recommended proportions (as per IS 9103), if approved in Mix design to accelerate or retard setting of concrete and / or improve workability with our impairing strength and durability compel as per	8,329.59	Cum	29811603

specification and direction of the Engineer in Charge. The rates inclusive of all material (except for steel Reinforcement), labour, T&P and Machinery, cantering and shuttering, mixing, loading, transporting, leading, lifting pumping etc required for execution of work. Payment of reinforcement shall be paid extra.

Note:

- 1. The concrete structures which are partially completed may have old reinforcements projecting out of these structures which may be main reinforcement/any other reinforcement which will become the integral part of bridge structure after completion. Prior to start of new reinforcement binding with old reinforcement. The old reinforcement shall be cleaned with wire brush to remove any dust etc., old reinforcement shall be treated with anti-corrosive coating. The anti-corrosive coating product shall be got approved from Employer's representative/Employer. No additional payment for old reinforcement cleaning/treatment will be paid.
- If at any structure old reinforcement is more corroded or reinforcement is cut or unavailable then new reinforcement shall be provided duly making drilling, providing coupling and provision of

	T				
		epoxy grouting etc. The payment for new reinforcement will be made separately however no payment will be made for drilling/joining/epoxy grouting, coupling etc.			
16	50	Providing and laying in position machine mixed, machine vibrated and machine batched Design mix cement concrete M 50 grade (cast -in situ) using 20 mm graded crushed stone aggregate and coarse sand of approved quality in RCC work for various components of Bridges like Deck slab for RCC Box Girder etc including finishing using Admixture in recommended proportions (as per IS 9103), if approved in Mix design to accelerate or retard setting of concrete and / or improve workability with our impairing strength and durability compel as per specification and direction of the Engineer in Charge. The rates inclusive of all material (except for steel Reinforcement), labour, T&P and Machinery, cantering and shuttering, mixing, loading, transporting, leading, lifting pumping etc required for execution of work. Payment for reinforcement shall be paid extra	8,329.59	Cum	416480
17	628	Providing, cutting, bending, hooking binding soft 16 SWG GI wires and fixing in position Thermo Mechanically Treated bar (TMT) Fe500 D reinforcing bars (SAIL/RINL /TISCO/ESSAR/JINDAL only), confirming to IS 1786, of various diameters for the RCC works in various	69,790.12	MT	43828195

		components of bridges structures such as raft, piers, pier cap, abutment, abutment cap, wing/return walls, toe walls, Girders, slabs, pedestals, stoppers, trolley refuges. RCC Box etc. as per detailed designs and drawings schedule, with Contractor's labour, material, T&Ps, Machinery & Fuel including all lead, lift and transportation, all complete as per specification and as directed by Engineer. The rate includes coast of 16 SWG GI. Wires.			
18	628	Providing and applying (mechanically sprayed) cement polymer composite coating (CPCC) of approved quality (confirming to CECRI) without hindrance the prevailing property of bond strength, on thoroughly cleaned by abrasive cleaning of surface of all the embedded reinforcement present in the surround concrete, before sufficient time of their placement, including cleaning of surface from mil scales, dust, rust and oily products if any etc. complete as directed by the Engineer in charge.	6,205.00	MT	3896740
19	660	Providing weep holes by keeping suitable length of 100 mm dia. PVC pipe in Reinforced concrete abutment, wing wall/return wall at interval as specified in drawing etc. complete	173.74	Meter	114668
20	524	Providing & casting in situ controlled machine mixed cement concrete M-35 for average 40 mm thick wearing coat laid as directed including tamping, vibrating finishing curing & filling in	6,312.97	Cum	3307996

		joint by as may be directed by Engineer in charge & as per the details specification by VDS/Trimix excluding coast of reinforcement but including cost of cement.			
21	8530	Providing two coats of anticorrosive coal tar epoxy Hi Build compound over one primer coat of epoxy zinc phosphate with all lead and lift with all labour, material tools & plants etc. complete	168.78	Sqm	1439693
22	36494	Providing protective coating to exposed concrete face of bridge as CECRI, Karalkudi - Integrated 4 coat system having 1st coat of micaceous iron oxide under coat, second coat polyimide primer, third coat of polyimide finish coat and last coat aliphatic acrylic polyethene finish coat (Bergethane or similar paint) as per specification.	242.00	Sqm	8831548
23	552	Manufacturing, Supplying and fixing in position of Vertical Bearing of size 300 x 160 x 22 mm with back plate, sleeves bolts, washers etc. The rate shall include cost of load test of one No. bearing from DFCCIL approved firms, inspection during manufacture and all fixing materials, equipment's, machineries, labour, taxes, loading, unloading, leading, lifting, etc. complete. Reference drawings No.PP/SOMA_DFCC/BOX/35 TON-TYPE-B, No.PP/SOMA_DFCC/BOX/40 TON-TYPE-A, No.PP/SOMA_DFCC/BOX/40 TON-TYPE-B, No.PP/SOMA_DFCC/BOX/50 TON-TYPE-A,	5,040.00	Per Nos.	2782080
24	1	Site Office Providing, arranging, managing and maintaining 500 sq.ft.	5,00,000	LS	5,00,000

		well furnished AC office and well			
		equipped Laboratory with 3 tables, 10			
		chairs, 2 steel almirah, one computer			
		with printer & operator, sufficient			
		number of display etc. to the			
		satisfaction of the Project Manager			
		including Electrical, Water expenses			
		etc. For execution of this item the date			
		of start shall be considered only when			
		the Contractor has rented /constructed			
		the required premises established the			
		office & Laboratory as per			
		requirement. This item shall remain			
		valid only for original contact period;			
		no additional payment shall be made			
		for whatsoever reason even if time			
		extension if provided or date of			
		completion is extended. This office and			
		laboratory including furniture and all			
		other equipment shall be property of			
		contractor after completion of Project.			
		This office shall be provided at bridge			
		no. 417.			
25	20	Providing & fixing shoring for	8,543.00	MT	170860
		protection of Railway embankment			
		with steel sheet piles/steel plates,			
		channels, I section, bolt & nuts with all			
		Contractor's material, labour, tools &			
		plants with all lead & lift including			
		excavation concreting, dewatering is			
		any required for flooring including			
		strutting & removing the shoring when			
		not required.			
		Note: -			
		1. This item will be operated only for			
		protection of existing embankment of Railway track for extension of bridge			
		having embankment height more			
		than 3.00 m.			
		2. Contractor shall provide detailed			

		Total Amount of Schedule - C		Rs. 13,4	9,12,385.00
					0.40.00= 00
		launching of girder			
		launching methology shall be got approved from DFCCIL before			
		instruction of engineer in charge. The			
		and place the girder in proper level/position and alignment as per			
		girders already casted by other agency) and place the girder in proper		Giraci	
27	2	Launching of PSC box/I Girder (those	109828.50	Per Girder	219657
27	2	White paper prints.	100020 50	Don	210057
		copy of the same on a CD, 6 blue /			
		alternations in red ink, along with a			
		duly incorporating all additions and			
		superior quality) in black indelible ink			
		(min. 75 microns thick, one side mat of			
		work, on polyester based tracing films			
		detailed drawings) after completion of			
		sets of completion drawings (all			
26	200	Preparing and submitting to Railways, 1	2,002.00	Sqm	400400
	200	done only in sanction traffic block.	0.000.00		400.77
		within 6.00 m existing track shall be			
		decision is final and binding. 6. Erection and dismantling of shoring			
		discretions of Engineer In charge. His			
		5. Execution of this item is solely on			
		property of the Contractor.			
		material of shoring will be the			
		4. After completion of work released			
		design whichever is less.			
		member required as per approved			
		member shall be restricted to size of			
		for shoring. The weight of structural			
		3. The mode of measurement for this item is weight of structural steel used			
		Railway Engineer.			
		erection scheme for approval of			
		detailed design calculation and			
		drawing of shoring supported with			

Schedule- D

		Description	Amount in Rs.
1.	USSOR	USSOR of W. Rly. items requiring for successful completion of the work as advised by in-charge of the work.	50,00,000.00
	Total Amount of Schedule – D		Rs. 50,00,000.00
	Total of Schedule A, B, C & D		Rs. 69,62,24,222.00

END OF TENDER DOCUMENTS